

Facade/wall Patching: ODB4

- Wall box indoor/outdoor
- Splicing up to 8 splices
- Patching up to 4 adapters SC type
- Lockins system with screw

The ODB4 optical distribution box is designed for indoor or façade distribution of a feeder cable to subscribers for FTTH deployments.

Main functions

- Clamping* of a Ø 12mm max. feeder cable at the bottom
- Clamping* of up to 4 subscriber cables (drop) Ø 4.5mm max. at the bottom
- Management and protection of fibres and up to 8 splices
- Indoor or outdoor wall mounting
- Cover securisation with a Torx T30 type screw (key provided)

* Clamping by plastic collars (not provided)

Composition

The ODB4 incorporates an organiser equipped with a swivelling and removable adapters support (not compatible with splitter integration).

The cover is secured with a Torx T30 type screw (key supplied).

Cabling

ODB4 is optimised for terminating installation.

In the organiser, various coiling areas make it possible to manage the bundles and the 900µm fibres, connected or waiting, avoiding any incident when connecting a new subscriber.

The organiser is compatible with G652D fibre. It allows the use of SOD splitters, mechanical splices and field connectors.


The splice holder is removable and can be replaced with an ANT splice holder (capacity of 12 splices).

Accessory - ANT splice holder



STANDARDS

IEC 61753-1



Accessory - ODB4 pole fixing

##image:113504##

These accessory is necessary to fix the ODB4 box on pole with metallic collar (not provided) or with screws (wooden pole only, not provided)

The kit is composed with 2 T plates and 4 screws to fix T plates on box from inside.

Aginode reference : **10279895**

Facade/wall Patching: ODB4

CHARACTERISTICS

Construction characteristics

Colour	Light grey RAL 7035
Cable entry	From the bottom
Material	Polycarbonate

Dimensional characteristics

Depth	45 mm
Height	175 mm
Width	145 mm
Splice number	8
Maximum number of adaptators	4

Mechanical characteristics

IK Rating	7
-----------	---

Usage characteristics

Operating temperature, range	-25...70 °C
Flame retardant	UL94-V2
U.V resistance	Yes
Installation type	Indoor/Outdoor
Watertightness	IP 55

Resources

ドキュメンテーション

Instruction manual ODB4 pdf — 2.05 MB [ダウンロード](#) ↓

Product list

	Aginode ref.	Country ref.	名前
☎	10278724	-	ODB4 without connectivity
☎	10280081	-	ODB4, equipped ANT, without connectivity

☎ = Make to order, 📦 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.