
LANmark-OF TB LSZH 2-24C - アジア太平洋地域

タイトバッファ光ファイバーケーブル

- バックボーン／水平配線用に設計された屋内用ケーブル
- すべてのファイバーグレードに対応
- 低煙・ハロゲンフリー（LSZH）





製品説明および用途

Aginode LANmark-OF TB
屋内用光ファイバーケーブルは、屋内用途向けに設計されています。本ケーブルは、伝送媒体の周囲に難燃性シースを備えた900μmのタイトバッファファ
本ケーブルは、強度材としてアラミド糸で被覆されており、最外層にはLSZHジャケットが施されています。曲げ耐性に優れたOM3/OM4およびシングルモ

本光ファイバーケーブルは、水平または垂直設置に適したドライ構造を採用しています。屋内防火要件を満たしており、ダクト内への設置が可能です。

- 垂直・水平の両方の設置が可能
- 標準的なマルチモードおよびシングルモードファイバーとして適用可能
- LSZHジャケット
- 被覆剥離が容易なタイトバッファファイバー

構造

2〜24芯OFケーブルの断面図に付随する凡例：

1. 900μm タイトバッファードファイバー
2. アラミド糸
3. LSZHジャケット材料

STANDARDS

ANSI/TIA-568-C.3
IEC 60332-1
IEC 60332-3-24 Cat.C
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF TB LSZH 2-24C - アジア太平洋地域

CHARACTERISTICS

Construction characteristics	
Fiber optic type	SM (G.652D)
Colour	Yellow
Dimensional characteristics	
Number of optical fibres	4
Outer Diameter	5.2 mm
Mechanical characteristics	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	800 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Usage characteristics	
Installation temperature, range	0...40 °C
Storage temperature, range	-30...70 °C
Operating temperature, range	-20...60 °C
Minimum dynamic operating bending radius	104.0 mm
Minimum static operating bending radius	52 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	名前
	N174.021	-	LANmark-OF タイトバッファ LSZH SM G.652.D 4C イエロー
	N177.020	-	LANmark-OF タイトバッファ LSZH OM4 2C アクア
	N174.025	-	LANmark-OF タイトバッファ LSZH SM G.652.D 12C イエロー
	N177.022	-	LANmark-OF タイトバッファ LSZH OM4 6C AQUA
	N174.020	-	LANmark-OF タイトバッファ LSZH SM G.652.D 2C イエロー
	N174.022	-	LANmark-OF タイトバッファ LSZH SM G.652.D 6C イエロー
	N175.021	-	LANmark-OF タイトバッファ LSZH OM3 4C オレンジ
	N175.025	-	LANmark-OF タイトバッファ LSZH OM3 12C オレンジ
	N175.031	-	LANmark-OF タイトバッファ LSZH OM3 24C オレンジ
	N177.023	-	LANmark-OF タイトバッファ LSZH OM4 8C アクア
	N177.021	-	LANmark-OF タイトバッファ LSZH OM4 4C アクア
	N175.022	-	LANmark-OF タイトバッファ LSZH OM3 6C オレンジ
	N175.023	-	LANmark-OF タイトバッファ LSZH OM3 8C オレンジ
	N174.023	-	LANmark-OF タイトバッファ LSZH SM G.652.D 8C イエロー
	N174.031	-	LANmark-OF タイトバッファ LSZH SM G.652.D 24C イエロー
	N177.025	-	LANmark-OF タイトバッファ LSZH OM4 12C アクア
	N177.031	-	LANmark-OF タイトバッファ LSZH OM4 24C アクア
	N175.020	-	LANmark-OF タイトバッファ LSZH OM3 2C オレンジ

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.