LANmark-OF MPO-MPO パッチコード

- AginodeのMPOパッチコードは、外径3mmのスリムなケーブル設計を採用しており、これによりデータセンターのユーザーは、パネル前面
- AginodeのMPOコネクタの光性能は業界水準を上回り、国際規格に準拠しています
- シングルモードおよび曲げ耐性のあるOM3/OM4に対応しています
- TIA 568.C.3に準拠したストレート極性（タイプB）
- 両端にメス型MPOコネクタを採用



STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

用途

AginodeのMPOパッチコードは、40G、100G、200G、400Gなどのデータセンター向け高速ネットワークアプリケーションに対応するように設計されています。このMPOケーブルは外径（OD）が最適化されており、優れた引張強度と耐圧性能を維持しています。各MPOトランクには、性能を保証するために工場発行の試

- MPOコネクタは、IEC 61754-7-1およびGR-1435-CORE規格に準拠しています。
- マルチモード用MPOコネクタはPC、シングルモード用MPOコネクタはAPCです
- OFケーブルはIEC 60794規格に準拠しています
- ケーブルはLSZH素材を採用しており、IEC 60332-1、IEC 50332-3-24、IEC 61034-2、およびIEC 60754-1・2に準拠しています。
- ファイバーは、IEC 60793-2-10（A1a.2b OM3 および A1a.3b OM4）、IEC 60793-2-50（B6_a1）、および ITU-T G.657 に準拠しています。シングルモード用 A1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO パッチコード

CHARACTERISTICS

Construction characteristics

Fiber optic type	OM4 50/125

Transmission characteristics

Insertion Loss, maximum, dB	0.25 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	名前
	N125.7SUV2	-	LANmark-OF MPO-MPO パッチコード、OM4、ストレート、MPO メス-MPO メス、12芯、LSZH、バイオレット、超低損失、2m
	N125.7SLV2	-	LANmark-OF MPO-MPO patch cord, OM4, Straight, MPO Female-MPO female, 12core, LSZH, Aqua, Low loss, 2m
	N125.4SLY2	-	LANmark-OF MPO-MPO パッチコード、OS2 APC、G.657.A1、ストレート、MPO メス-MPO メス、12コア、LSZH、黄色、低損失、2m
	N125.5SLA2	-	LANmark-OF MPO-MPO パッチコード、OM3、ストレート、MPOメス-MPOメス、12芯、LSZH、アクア、低損失、2m

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.