LANmark-OF UC PE（ユニチューブ・スチール・アーマリング）

UC光ファイバーケーブル

- 屋外ダクトまたは直接埋設
- 波型スチールテープアーマー
- すべてのファイバー・グレードで利用可能
- 完全なネズミ対策を提供



説明と応用

屋外でのダクトや直接埋設に適しています。完全な防鼠効果を発揮する波型鋼テープアーマーで構成されています。周囲はガラス糸で覆わ
ファイバー径は250umで、終端はピッグテールで接続する。
ケーブルは、ルースチューブ内のゲルと防水ガラスヤーンにより防水性がある。



特性

- ダクト内または直接埋設用の屋外ケーブル
- スプライシングによる終端用に設計
- 中央ルースチューブ設計
- 波型スチール保護
- 防水構造、防鼠、UV耐性
- すべてのファイバーグレードで利用可能
- 4-24ファイバーから選択可能

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

CHARACTERISTICS

Construction characteristics

Construction type	Loose Tube
Fiber optic type	SM (G657.A1)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	名前
N164.UCPE06B	-	LANmark-OF UC 6x Singlemode 9/125 OS2 PE Black
N164.UCPE12B	-	LANmark-OF UC 12x Singlemode 9/125 OS2 PE Black
N164.UCPE24B	-	LANmark-OF UC 24x Singlemode 9/125 OS2 PE Black
N165.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM3 PE Black
N165.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black
N165.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM3 PE Black
N167.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM4 PE Black
N167.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM4 PE Black
N167.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.