# LANmark WDZ-RYYP CU/LSZH/OS(TC)/LSZH
# シールド付き難燃性フレキシブルケーブル

LANmarkシリーズの低電圧ケーブルは、通信、信号伝送、およびセキュリティ機器の低電圧電源供給用に設計された専用ケーブルです。
これらのケーブルは、公共のセキュリティ、監視プロジェクト、商業ビル、住宅、スマートホーム、およびイ[illegible]ビルシステム



## 特徴

- 銅（クラス5）
- 着色ポリオレフィン絶縁
- LSZHジャケット
- 錫メッキ銅線シールド
- 公称電圧：U0/U=300/300V
- 温度範囲：動作時：-20°C～70°C

設置時：0°C ～ 50°C

絶縁体色

| 芯数 | 色 |
|---|---|
| 2 | 青、赤 |
| 3 | 青、赤、黄／緑、または青、赤、緑 |
| 4 | 青、赤、緑、黄／緑、または青、赤、緑、黄 |
| 5 | 青、赤、緑、黄、黄／緑、または青、赤、緑、黄、黒 |
| 6 | 青、赤、緑、黄、黒、黄緑、または青、赤、緑、黄、黒、茶色 |
| 7 | 黄/緑の芯線を除く、番号付き黄色のジャケット。 |

注：芯線の組み合わせに黄緑色のアース線が含まれる場合、Nコードには接尾辞「G」を追加する必要があります。断面積の表記では、「x

## STANDARDS

IEC 60228
IEC 60754
IEC 61034
IEC 60332-1

## 技術データ

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| N – Code | Type | Cross section (mm²) | Insulation (mm) | Sheath (mm) | General OD. max | General OD. mix | Conductor Resistance 20°C / Ω/km | Insulation Resistance 70°C / MΩ.km |
|---|---|---|---|---|---|---|---|---|
| N10R13YWP205 | WDZ-RYYP | 2x0.5 | 0.5 | 0.6 | 5.7 | 7.7 | 39.0 | 0.013 |
| N10R13YWP305 | WDZ-RYYP | 3x0.5 | 0.5 | 0.6 | 6.0 | 8.0 | 39.0 | 0.013 |
| N10R13YWP405 | WDZ-RYYP | 4x0.5 | 0.5 | 0.6 | 6.6 | 8.6 | 39.0 | 0.013 |
| N10R13YWP505 | WDZ-RYYP | 5x0.5 | 0.5 | 0.6 | 7.1 | 9.1 | 39.0 | 0.013 |
| N10R13YWP605 | WDZ-RYYP | 6x0.5 | 0.5 | 0.8 | 7.7 | 9.7 | 39.0 | 0.013 |
| N10R13YWP705 | WDZ-RYYP | 7x0.5 | 0.5 | 0.8 | 7.7 | 9.7 | 39.0 | 0.013 |
| N10R13YWP805 | WDZ-RYYP | 8x0.5 | 0.5 | 0.9 | 8.6 | 10.6 | 39.0 | 0.013 |
| N10R13YWP207 | WDZ-RYYP | 2x0.75 | 0.5 | 0.6 | 6.0 | 8.0 | 26.0 | 0.011 |
| N10R13YWP307 | WDZ-RYYP | 3x0.75 | 0.5 | 0.6 | 6.4 | 8.4 | 26.0 | 0.011 |
| N10R13YWP307G | WDZ-RYYP | 3G0.75 | 0.5 | 0.6 | 6.4 | 8.4 | 26.0 | 0.011 |
| N10R13YWP407 | WDZ-RYYP | 4x0.75 | 0.5 | 0.8 | 7.0 | 9.0 | 26.0 | 0.011 |
| N10R13YWP507 | WDZ-RYYP | 5x0.75 | 0.5 | 0.8 | 7.6 | 9.6 | 26.0 | 0.011 |
| N10R13YWP607 | WDZ-RYYP | 6x0.75 | 0.5 | 0.8 | 8.2 | 10.2 | 26.0 | 0.011 |
| N10R13YWP707 | WDZ-RYYP | 7x0.75 | 0.5 | 0.8 | 8.2 | 10.2 | 26.0 | 0.011 |
| N10R13YWP807 | WDZ-RYYP | 8x0.75 | 0.5 | 0.8 | 9.2 | 11.2 | 26.0 | 0.011 |
| N10R13YWP210 | WDZ-RYYP | 2x1.0 | 0.6 | 0.6 | 6.8 | 8.8 | 19.5 | 0.010 |
| N10R13YWP310 | WDZ-RYYP | 3x1.0 | 0.6 | 0.8 | 7.2 | 9.2 | 19.5 | 0.010 |
| N10R13YWP410 | WDZ-RYYP | 4x1.0 | 0.6 | 0.9 | 7.9 | 9.9 | 19.5 | 0.010 |
| N10R13YWP510 | WDZ-RYYP | 5x1.0 | 0.6 | 0.9 | 8.6 | 10.6 | 19.5 | 0.010 |
| N10R13YWP610 | WDZ-RYYP | 6x1.0 | 0.6 | 1.0 | 9.6 | 11.6 | 19.5 | 0.010 |
| N10R13YWP710 | WDZ-RYYP | 7x1.0 | 0.6 | 1.0 | 9.6 | 11.6 | 19.5 | 0.010 |
| N10R13YWP810 | WDZ-RYYP | 8x1.0 | 0.6 | 1.0 | 10.7 | 12.7 | 19.5 | 0.010 |
| N10R13YWP215 | WDZ-RYYP | 2x1.5 | 0.6 | 0.8 | 7.4 | 9.4 | 13.3 | 0.010 |
| N10R13YWP315 | WDZ-RYYP | 3x1.5 | 0.6 | 0.8 | 7.8 | 9.8 | 13.3 | 0.010 |
| N10R13YWP415 | WDZ-RYYP | 4x1.5 | 0.6 | 0.9 | 8.6 | 10.6 | 13.3 | 0.010 |
| N10R13YWP515 | WDZ-RYYP | 5x1.5 | 0.6 | 1.0 | 9.6 | 11.6 | 13.3 | 0.010 |
| N10R13YWP615 | WDZ-RYYP | 6x1.5 | 0.6 | 1.0 | 10.4 | 12.4 | 13.3 | 0.010 |
| N10R13YWP715 | WDZ-RYYP | 7x1.5 | 0.6 | 1.0 | 10.4 | 12.4 | 13.3 | 0.010 |
| N10R13YWP815 | WDZ-RYYP | 8x1.5 | 0.6 | 1.0 | 11.7 | 13.7 | 13.3 | 0.010 |
| N10R13YWP225 | WDZ-RYYP | 2x2.5 | 0.7 | 1.0 | 8.9 | 10.9 | 7.98 | 0.009 |
| N10R13YWP325 | WDZ-RYYP | 3x2.5 | 0.7 | 1.0 | 9.4 | 11.4 | 7.98 | 0.009 |
| N10R13YWP425 | WDZ-RYYP | 4x2.5 | 0.7 | 1.0 | 10.4 | 12.4 | 7.98 | 0.009 |
| N10R13YWP525 | WDZ-RYYP | 5x2.5 | 0.7 | 1.1 | 11.5 | 13.5 | 7.98 | 0.009 |
| N10R13YWP625 | WDZ-RYYP | 6x2.5 | 0.7 | 1.1 | 12.6 | 14.6 | 7.98 | 0.009 |

注：芯線の組み合わせに黄緑色のアース線が含まれる場合、Nコードには接尾辞「G」を追加する必要があります。断面積の表記では、「x

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

## Product list

| Aginode ref. | Country ref. | 名前 |
|---|---|---|
| N10R13YWP707 | - | LANmark WDZ-RYYP 7×0.75mm² CU/LSZH/OS(TC)/LSZH、シールド付き難燃性フレキシブルケーブル、黒 |

= Make to order, = In Stock

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*