LANmark-OF MPO-MPO ファイバーパッチコード OFNP

- AginodeのMPOパッチコードは、外径3mmのスリムなケーブル設計を採用しており、これによりデータセンターのユーザーは、パネル前面
- AginodeのMPOコネクタの光性能は業界水準を上回っており、国際規格に準拠しています。
- 12F屋内用フレキシブル光ケーブル
- シングルモードおよび曲げ耐性のあるOM3/OM4に対応
- 難燃性能は、UL 1651に基づくOFNP規格に準拠しています
- TIA 568.3-E 規格に準拠したストレート極性（タイプ B）、キーアップ/キーアップ配向
- 両端にメス型MPOコネクタを装備



STANDARDS

ISO/IEC 11801
ANSI/TIA-568.3-D

用途

AginodeのMPOパッチコードは、40G、100G、200G、400Gなどのデータセンター向け高速ネットワーク用途に対応するように設計されて
このMPOケーブルは外径（OD）が最適化されており、優れた引張強度と耐圧性能を維持しています。各MPOトランクには、性能を保証す

特長

- MPOコネクタはIEC 61754-7-1およびGR-1435-CORE規格に準拠
- マルチモード用MPOコネクタはPC、シングルモード用MPOコネクタはAPCです
- 難燃性能は、UL 1651に基づくOFNP規格に準拠しています
- ファイバーは、IEC 60793-2-10（A1a.2b OM3 および A1a.3b OM4）、IEC 60793-2-50（B6_a1）、および ITU-T G.657 に準拠しています。シングルモード用はA1です。

光性能および極性

- 超低損失マルチモード MPO コネクタの標準挿入損失は 0.2 dB、最大挿入損失は 0.35 dB です。
- 低損失シングルモード MPO コネクタの標準的な挿入損失は 0.35 dB で、最大挿入損失は 0.5 dB です。
- MPO コネクタの挿入損失は、規格 IEC 61300-3-45 に準拠して測定されます。
- マルチモードMPO接続の最小反射損失は20 dBです。シングルモードMPO接続の最小反射損失は55 dBです。測定はIEC 61300-3-6に準拠しています。

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO ファイバーパッチコード OFNP

CHARACTERISTICS

Dimensional characteristics

Number of optical fibres	12

Usage characteristics

Operating temperature, range	-20...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	名前
N125.7SUAxxxNP	-	LANmark-OF MPO パッチコード OM4 メソッドB MPO12/PC メス - MPO12/PC メス 12芯 LSZH アクア 超低損失 10m
N125.7SUVxNP	-	LANmark-OF MPO-MPO パッチコード、OM4、ストレート、MPOメス-MPOメス、12芯、OFNP、バイオレット、超低損失、xm
N125.7J10SUVxxxNP	-	LANmark-OF Base8 MPO パッチコード、16F MPO/APC メス - 2x8 MPO/UPC メス、OM4、400G 極性、OFNP、バイオレット、超低損失、xm
N125.4SUYxNP	-	LANmark-OF MPO-MPO パッチコード、OS2 APC、G.657.A1、ストレート、MPO メス-MPO メス、12芯、OFNP、黄色、超低損失、xm

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.