Modular Patch Panels for Snap-In Connectors

PATCH PANEL 24 SNAP-IN FIXED BLACK



Aginode Ref: N521.661BK

- Compatible with all LANmark Snap-In connectors
- 24 Snap-In ports with shutters
- Clip-on mechanism
- Exclusive Auto-Connect Earthing system
- Universal design supporting Unscreened and Screened connectors
- Also available in white

Aginode Snap-In range of patch panels are designed to accomodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The patch panels are designed for standard 19" enclosures, are 1U high, and support the following common features:

- 24 Ports with shutters
- Designed for Screened and Unscreened Snap-In connectors
- Compatible with all performance categories of connector
- Clip-On mechanism for simple earthing
- Exclusive rear cable management facilities
- Robust construction
- Printed numbering for port labelling

This panel features vertical "T" clips for rapid cable retention which allows loading of the panel in around 25% of the time needed to fasten tie wraps which leads to time saving during installation.

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Patch Panel 24 Snap-In Fixed Black

Characteristics

Construction characteristics	
Colour	Black
Material	Steel
Dimensional characteristics	
Depth	75 mm
Width	19 inches
Approximate weight per piece	0.65 kg
Heightunit	1 U
Usage characteristics	
Field of application	Fixed installations
Number of ports	24
Mechanical Resistance	Good mechanical resistance
Packaging	Box
Resistance to vibrations	High

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.