

LANmark Industry DIN-Rail Outlets and boxes

LANMARK INDUSTRY MODULE DIN-RAIL MOUNT WITH 1 SNAP-IN CATEGORY 6 GREY - DISCONTINUED

Aginode Ref: N20i.000

- For DIN-Rail mount (35mm)
- Data connection for the industry
- Easy termination, without punch down tool.
- Includes Mount + LANmark-6 shielded connector
- For technical enclosures, Wireless Access Points, Industrial cabinets

Application

The LANmark Industry DIN-Rail mount is designed to enable the installation of LANmark-6 Snap-in data connectors in industrial cabinets fitted with a 35mm DIN-Rail. Several DIN-Rail mounts can be joined together to form a row. The LANmark-6 connector exceeds the requirements of the ISO/IEC 11801:2002. As such it supports all data applications defined for Cat 5, Cat 5e and Cat 6, such as:

- 10baseT
- Fast Ethernet
- Gigabit Ethernet
- 155 ATM
- 622 ATM
- 1.2 ATM
- Industrial Ethernet


Performance

The LANmark-6 Snap-in connector has been designed to reach the highest performance in Category 6. It has been tested as specified in the TIA/EIA-568-B.2-1, the IEC 60603-7-5 (screened) standards. Furthermore, it complies with the Terms and conditions for use of the EC Verified marking on generic cabling products, as certified by Delta independent testing.

Installation

The LANmark-6 Snap-in connector is designed to be terminated without punchdown tool. For fast and easy installation an optional comfort tool can be used.

- Fast termination
- Colour code : TSB568A & TSB568B



STANDARDS

IEC 60603-7-5
ISO/IEC 11801
ISO/IEC 24702

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- Can be used with all types of cables : UTP, F/UTP, SF/UTP and S/FTP
- Accepts 24, 23 and 22 AWG cable, PUR, LSZH
- For all LANmark industrial cables

LANmark Industry module DIN-rail mount with 1 Snap-In Category 6 grey - DISCONTINUED

Characteristics

Construction characteristics

Cable entry	From the top
Colour	Grey
Connector type	RJ 45
Material	ABS
Screen	Yes

Dimensional characteristics

Approximate weight per piece	0.03 kg
Depth	65 mm
Dimensions of screw	N/A
Height	77.8 mm
Length cable end on inner side	80.0 mm
Number of cables	1
Wall thickness	1.6 mm
Width	18 mm

Electrical characteristics

Characteristic impedance	100 Ohm
Maximal operating frequency	250 MHz

Mechanical characteristics

Mechanical resistance to impacts	Low
----------------------------------	-----

Usage characteristics

Category	Cat. 6
Component function	Cabling and Connectivity solutions
Electro magnetic interference resistance	Yes
Field of application	Industrial installations
Maximum operating temperature	70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Number of ports	1
Packaging	Plastic bag
RoHS compliant	Yes
Water proof	No

ドキュメンテーション

Freetable LM6 conn.xls xls — 13.5 KB [ダウンロード ↓](#)

販売および配送情報

The LANmark-6 DIN-Rail Mount is fitted with a earth tag for termination of the cable drain wire / shield - to provide a grounding connection to the DIN-Rail. Please see installation guide. A set of covers for both sides of the module is also available (N20i.002).