

# LANsense Copper Patch Cords

## LANSENSE PATCH CORD CAT 6A LSZH SCREENED

**Aginode Ref:** N88A.P1F0500K

- 9th pin for port detection
- Ensures maximum channel performance
- Cat 6A/10G
- screened
- Alternative lengths available

The Aginode LANsense patchcord range is suitable for use in voice or data network installations. The 4 pair construction and robust RJ45 connectors provide for long term network reliability. The patchcords have an unobtrusive external probe built into the plug boot which mates with the sensors built into the patch panels. The patchcords can be supplied in different lengths and with different colour latch protectors to allow differentiation of services and workgroups.



### STANDARDS

EN 50265-2-1  
ISO/IEC 11801

# LANsense Patch Cord Cat 6A LSZH Screened

## Characteristics

### Construction characteristics

|              |        |
|--------------|--------|
| Colour       | Orange |
| Screen       | FTP    |
| Outer sheath | LSZH   |

### Dimensional characteristics

|                             |        |
|-----------------------------|--------|
| Nominal outer diameter (mm) | 6.0 mm |
|-----------------------------|--------|

### Usage characteristics

|                    |           |
|--------------------|-----------|
| Range              | LANsense  |
| Length             | 5 m       |
| Category           | Cat. 6A   |
| Component function | Patchcord |