LANsense Copper Patch Cords

LANSENSE PATCH CORD CAT 6 LSZH SCREENED



Aginode Ref: N886.P1F010OK

- 9th pin for port detection
- Ensures maximum channel performance
- Cat 6
- screened
- Alternative lengths available

The Aginode LANsense patchcord range is suitable for use in voice or data network installations. The 4 pair construction and robust RJ45 connectors provide for long term network reliability. The patchcords have an unobtrusive external probe built into the plug boot which mates with the sensors built into the patch panels. The patchcords can be supplied in different lengths and with different colour latch protectors to allow differentiation of services and workgroups.

STANDARDS

EN 50265-2-1
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANsense Patch Cord Cat 6 LSZH Screened

Characteristics

Construction characteristics	
Colour	Orange
Screen	FTP
Outer sheath	LSZH
Dimensional characteristics	
Nominal outer diameter (mm)	6.0 mm
Usage characteristics	
Range	LANsense
Length	1 m
Category	Cat. 6
Component function	Patchcord

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.