


# Voice Cables APAC

## VOICE U/UTP 25 PAIR AWG24 CAT 3 LSZH ORANGE REEL

**Aginode Ref:** N100.817N

- Unshielded Cat 3 cable
- 25 pairs
- Suitable for voice and low grade data applications in LAN infrastructure
- Orange LSZH outer sheath

Voice grade cables are used to integrate telephony applications in the backbone of a LAN infrastructure. They are multipair twisted pair cables and exist in Category 3, Category 5 and Category 5e performance levels.



### STANDARDS

ANSI/TIA-568-C.2  
ISO/IEC 11801

# Voice U/UTP 25 pair AWG24 Cat 3 LSZH Orange reel

## Characteristics

### Construction characteristics

Screen	No
Outer sheath	LSZH
Sheath colour	Orange
Insulating material	PE
Type of cable	U/UTP
Conductor material	Bare copper

### Dimensional characteristics

Number of pairs	25
Conductor cross-section (AWG/KCMIL)	24
Nominal outer diameter (mm)	11.0 mm

### Electrical characteristics

Mutual capacitance	66 nF/km
Characteristic impedance	100 Ohm

### Mechanical characteristics

Maximum pulling force (IEC 60794-1-2-E1)	300 N
--	-------

### Transmission characteristics

Attenuation at 16 MHz	13.1 dB/100m
Attenuation at 1 Mhz	2.6 dB/100m

### Usage characteristics

Operating temperature, range	-15...60 °C
Minimum dynamic operating bending radius	110.0 mm
Category	Cat. 3
Flame retardant	IEC 60332-1
Ambient installation temperature, range	0...50 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.