

# 120 System (4.75 inch)

## FIBREROUTE 120MM(4.75 INCH) EQUAL CROSS COVER

**Aginode Ref:** N350.120FA13A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Cover for 120mm(4.75 inch) Equal cross
- Tough, flame retardant ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Cover for the Equal Cross provides protection against dust and falling items.

All components of the system including the covers can be installed and uninstalled without special tools.



### STANDARDS

EN 50173-5  
ISO/IEC 24764  
UL 94 V0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# FIBREROUTE 120mm(4.75 inch) Equal Cross Cover

## Characteristics

### Construction characteristics

Material	ABS
Colour	Yellow

### Dimensional characteristics

Approximate net weight	0.1 kg
Length	352 mm

### Usage characteristics

Storage temperature, range	-45...60 °C
Operating temperature, range	-25...60 °C