LANmark-OF Aggregation Assembly MTP/F-4XDLC

LANMARK-OF アグリゲーションアセンブリ MTP/F-4XDLC 8XOM4 1M ファンアウト A XM バイオレット



Aginode Ref: N127.7FLAVx

- 工場成端ファイバーアセンブリ
- 4xユニブートDLCコネクタに向けたメスMTP付きファイバーアセンブリ
- スイッチのQSFP+トランシーバーに接続するためのメスMTPコネクター
- パッチパネル前面のパッチ用Uniboot DLCコネクタ
- パッチパネル上の4x 10Gチャンネルをスイッチ上の1x 40Gポートに集約
- ファイバータイプOM3およびOM4
- 8コア
- 低損失接続性能：接続あたり最大0.3 dB

構造

直径3.65
mmの丸型ケーブルの片側はメスMTP*コネクターで終端されている。もう片側はユニブート二重LCコネクターでファンアウト終端されて
ファンアウトポイントと各ユニブートコネクター間の長さは等しく、通常1m（ファンアウトA）または2m（ファンアウトC）です。MTP

ケーブルの曲げ半径は40mmと小さく、内部には曲げに弱いファイバーを使用しています。

このケーブルは難燃性（IEC 60332-1）および難燃性（IEC 60332-
3）です。

STANDARDS

ISO/IEC
11801:2002/Amd 1:2008/Cor 1:2008

アプリケーション

このアセンブリは、パッチパネルの前面から4X
10Gチャンネルをスイッチの1x
40Gポートに集約することができます。

メスMTPコネクターは、スイッチの40G
QSFP+ポート内のオスMTPコネクターに適合します。

性能

MTPコネクターは低損失です。低損失MTP-
MTP接続の挿入損失の標準値は0.125 dBです。規格IEC 61300-3-
45に従って測定した限界値は0.3 dBです。

一貫した品質

高品質で信頼性の高い終端処理済みマルチファイバーケーブルを製造するためには、多くの物理的特性に対応する必要があります。そのた
OF
プリタームはすべて、完全に終端され、品質が保証された工場環境でテストされます。
これらのテスト結果とともに納品されます。

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

* MTPはUS Conecの商品名です。

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF アグリゲーションアセンブリ MTP/F-4XDLC 8XOM4 1m ファンアウト A xm バイオレット

Characteristics

Construction characteristics	
Fiber optic type	OM4 50/125
Dimensional characteristics	
Nominal outer diameter (mm)	3.65 mm
Mechanical characteristics	
Crush resistance (IEC 60794-1-E3)	50 N/cm
Mechanical resistance to impacts	10 impacts of 1 N.m
Usage characteristics	
Fire retardant	IEC 60332-3
Flame retardant	IEC 60332-1
Minimum static operating bending radius	40 mm
Operating temperature, range	0...60 °C
Storage temperature, range	-20...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.