

Cat.6 450 F/UTP LSZH Dca

AGINODE C6 450 F/UTP LSZH DCA 4P 500M IVOIRY

Aginode Ref: 10269942

EAN: 3427630103593

- Complies to latest Cat 6 standard version
- Supports Class E applications
- Cable tested up to 450 MHz
- Flame retardant according to EN50575:2014+A1:2016 and IEC 60332-1
- Global screen for EMC performance
- Compatible POE, POE+ and UPOE
- RoHS EC Directive compliant
- Compliant with European Reach regulation
- N'Roll and MOBIWAY™ compatible

Application



F/UTP Category 6 cables are the standard offering from Aginode. Manufactured in accordance with ISO IEC 61156-5 requirements, the F/UTP cable is the best choice to support all Class E applications like Ethernet, Fast Ethernet, Gigabit Ethernet, ... Cat 6 F/UTP cables are suitable for basic voice and data installations up to 250 MHz. Aginode Cat.6 cables, combined with a similar class of performance connectivity, are suitable for voice and data installations according to ISO/IEC 11801, EN 50173 and TIA/EIA 568 standards.

Construction

1. Conductor: solid bare copper
2. Insulation : Polyethylen (EN 50290-2-23) - Two insulated conductors twisted to a pair
3. Cross filler - 4/2 laid up together
4. Tinned copper drain wire
5. Screen: ALU/PET foil - Alu inside
6. Outer Jacket : LSZH - Dca

Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation. The outer sheath of the cable is made of halogen free material (IEC 60754-1 / EN 50267-2-1),



STANDARDS

EN 50173
EN 50288
EN 50575
IEC 60332-1
IEC 61156-5
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

with limited fumes emission (IEC 61034-1/2 / EN 50268-1/2) and no acid gas emission in case of fire (IEC 60754-2 / EN 50267-2-2).

Aginode measure the environmental impact of each of the cable. Upon request the PEP Ecopassport or the Eco Material Declaration could be available.

Cat 6 450 F-UTP TRANSMISSION CHARACTERISTICS

CAT.6 450 F/UTP TRANSMISSION CHARACTERISTICS

Values at 20°C

Frequency (MHz)	S/T	4	10	16	20	100	200	250	350	450
Attenuation max. (dB/100m)	Standard	3.8	6.0	7.6	8.5	19.9	29.1	33.0	-	-
	Typical	3.6	5.5	6.9	7.7	17.6	25.4	28.6	34.4	39.5
NEXT min. (dB)	Standard	66.3	60.3	57.2	55.8	45.3	40.8	39.3	-	-
	Typical	80.5	72.7	68.8	66.9	53.3	47.4	45.5	42.7	40.5
PSNEXT min. (dB)	Standard	63.3	57.3	54.2	52.8	42.3	37.8	36.3	-	-
	Typical	77.5	69.7	65.8	63.9	50.3	44.4	42.5	39.7	37.5
ACRF min. (dB)	Standard	56.0	48.0	43.9	42.0	28.0	22.0	20.0	-	-
	Typical	85.5	76.3	71.5	69.3	53.1	46.1	43.9	40.5	38.0
PSACRF min. (dB)	Standard	53.0	45.0	40.9	39.0	25.0	19.0	17.0	-	-
	Typical	82.5	73.3	68.5	66.3	50.1	43.1	40.9	37.5	35.0
Return Loss min. (dB)	Standard	23.0	25.0	25.0	25.0	20.1	18.0	17.3	-	-
	Typical	27.0	29.0	29.0	29.0	24.5	22.5	21.9	20.9	20.2

AGINODE C6 450 F/UTP LSZH Dca 4P 500m IVOIRY

Characteristics

Construction characteristics

Outer sheath	LSZH
Sheath colour	Ivory
Halogen free	Yes
Higher heating value	821 MJ/km
Type of cable	F/UTP
Overall screen	Aluminium/polyester tape

Dimensional characteristics

Approximate weight	49 kg/km
Number of pairs	4
Conductor cross-section (AWG/KCMIL)	24
Diameter over insulation	1.13 mm
Nominal outer diameter (mm)	7.1 mm
External dimensions	Not applicable

Electrical characteristics

Mutual capacitance	50 nF/km
Max. DC resistance of the conductor at 20°C	95 Ohm/km
Characteristic impedance at 100 MHz	100 Ohm

Mechanical characteristics

Maximum installation tension	80 N
------------------------------	------

Transmission characteristics

Nominal Velocity of Propagation (NVP)	70 %
Coupling attenuation at 30 MHz	>50dB

Usage characteristics

Field of application	Fixed installations
Category	Cat. 6
Flame retardant	IEC 60332-1
Smoke density	Low

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Packaging	Drum 500 m
Ambient installation temperature, range	0...50 °C
Bending factor when laying	8 (xD)
Bending factor when installed	4 (xD)
Ambient static operating temperature, range	-20...70 °C

パフォーマンス宣言

AGINODE C6 450 F/UTP LSZH Dca 4P 500m IVOIRY pdf — 116.33 KB [ダウンロード ↓](#)