

Splicing Patching / POB 24-36-48

POB 24 RIGHT AXIS SUBRACK VERSION PRE-EQUIPPED WITH 12 SC

Aginode Ref: 10242128

POB 24 right axis subrack version

- Swivelling module for 19" or ETSI frames
- Full access to the back of the frame
- Combined functions: splicing and patching
- 12 SC/APC adaptors
- 12 SC/APC pigtails
- A primary fan-out device
- A KINOPTIC™ product

Application

The POB 24 1U is a module with combined splicing and patching functions. It is used to connect up to 24 fibres. On the terminal part of FTTH network, it is the transition element towards active equipment. The module is installed either in Central Office or in FTTH nodes. It can also be used as a distribution module.

Description


The POB 24 1U module includes a space reserved for splicing of the incoming fibres. Splicing is performed in splicing trays. A panel ensures the patching functions with a capacity of up to 24 connection points SC.

The module is compatible with all type of frames (19" or ETSI standards) with a minimum depth 300mm. This is a subrack version.

The accessories fitted with the module guarantee the conformity with the bending radius of the fibres (G652). It is prepared in order to minimise the installation time on sites where it is deployed.

The module is composed of the following subparts:

- Fixed chassis or envelope attached to the rack (19" or ETSI)
- Swivelling chassis (left or right versions are available) including a patch panel with alphanumeric identifier for the adaptors,
- Pivoting support to access the splice trays
- Device for lateral management of optical jumpers harnesses,
- A primary fan-out device.



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

The management of cables or protection tubes is done at the rear of the module whilst the management of the jumpers is performed at the front and on the rotation axis side.

POB 24 right axis subrack version pre-equipped with 12 SC

Characteristics

Construction characteristics

| | |
|----------------|---------------|
| Colour | RAL 9002 |
| Cabinet format | 19"/ETSI |
| Material | Steel painted |

Dimensional characteristics

| | |
|----------------------|--------|
| Depth | 200 mm |
| Height | 50 mm |
| Splice number | 48 |
| Cable Diameter | 18 mm |
| Heightunit | 1 U |
| Number of connectors | 12 |

Usage characteristics

| | |
|---|-------------|
| Operating temperature, range | -25...70 °C |
| Minimum static operating bending radius | 30 mm |
| Packaging | Box |