Railways - Multibundle K209 cables

MBC LSZH K209B 6XSM G652D SP1344 BK

Aginode Ref: 10548533

Multi Micro-bundles cable with corrugated steel armour - 6 fibres SM G652D




This multi micro-bundles cable is designed for indoor/outdoor installation in railways infrastructure.

The corrugated steel armour provides a high rodent protection. This cable has an outstanding fire behaviour.

Access to µbundles is made easy with the internal ripcord.

This cable can be operated under a large temperature range.



Design

The MBC LSZH* SP1344 cable has a central strength member (FRP : Fibre Reinforced Plastic), with bundle around integrating 6 fibres . The design is reinforced by a first layer of watertight glass, a LSZH* inner sheath, a second layer of watertight glass yarns, a corrugated steel armour and a LSZH* outer steath.

Fibre type

The MBC LSZH* SP1344 cable is available with singlemode fibres.

Technical performances

The multibundle cable performances are specified in the following tables.

Additional details

This cable is provided as a standard with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.

STANDARDS

EN 50399 B2
IEC 60331-2
IEC 60332-1
IEC 60332-3
IEC 60754-1
IEC 60794
IEC 61034
NF C32-070/C1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Euroclass

$B2^{ca}$ S1a a1 d0

* LSZH: Low Smoke Zero Halogen.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

MBC LSZH K209B 6xSM G652D SP1344 BK

Characteristics

Construction characteristics	
Colour	Black
Fiber optic type	SM (G.652D)
Armour type	Corrugated steel
Outer sheath	LSZH
Halogen free	IEC 60754-1
Material used for longitudinal water tightness	Swellable yarn
Metal free	No
Strength member	Central FRP
Construction type	Multibundle
Additional strength member	Glass yarn
Dimensional characteristics	
Number of tubes	1
Approximate weight	176 kg/km
Number of optical fibres	6
Nominal outer diameter (mm)	11.1 mm
Mechanical characteristics	
Mechanical resistance to impacts	10 impacts of 1 N.m
Maximum permanent tensile load	1.4 kN
Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum installation tension	2000 N
Transmission characteristics	
Attenuation, max. 1310 nm (cabled)	0.36 dB/1000m
Attenuation, max. 1550 nm (cabled)	0.23 dB/1000m
Usage characteristics	
Rodent protection	Corrugated steel tape
Operating temperature, range	-20...60 °C
Fire retardant	IEC 60332-3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Minimum static operating bending radius	220 mm
Flame retardant	IEC 60332-1
Smoke density	IEC 61034-2
U.V resistance	Good
Storage temperature, range	-20...70 °C
Laying operation bending radius	275 mm
Installation type	Indoor/Outdoor
Installation temperature, range	-20...60 °C
Water proof	Longitudinal & radial

パフォーマンス宣言

MBC LSZH K209B 6xSM G652D SP1344 BK pdf — 120.34 KB　ダウンロード

販売および配送情報

Standard Marking

Aginode - FIBRE OPTIC CABLE - MBC LSZH SP1344 - XXxYY - FB - TN - metric
XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.