

PRE: 24/48 Distribution Cabinet

PRE 48 OF

Aginode Ref: 10279411

Indoor / Outdoor Distribution Cabinet:

- version for up to 48 subscribers
- installation on wall, pole or stand alone with a metallic riser (optional)
- 1 cassette dedicated to splitters (patched or spliced)
- 8 cassettes for subscriber management
- suitable for PON as P2P network architectures

The PRE 48 is a distribution cabinet designed to adapt to as much ground configuration as possible. Its use makes it possible to reduce the complexity of the deployments by proposing a unique reference which can be fixed on a wall, a pole or a riser as an autonomous cabinet.

The PRE 48 can be used indoors as well as outdoors (IP55).

Capacity

This configuration is made to manage up to 48 OF. The number of cassettes, each accommodating up to 12 splices, is adapted to your needs and the network architecture used (PON or P2P).

Patching and splicing

3 separate zones make it possible to manage the body of the splitters (SOD), the connectors of the subscriber cables, and the coiling or splicing of the main and secondary cables (or pigtails). Depending on your needs, the PRE 48 can be configured in both patching and splicing versions.

Quality materials

While the body of the PRE 48 is made of polyester reinforced with fiberglass ensuring a lightness, waterproofness (IP55) and shock abatement (IK10), the moving parts are metallic to guarantee an optimal lifetime of the assembly when intensive uses.

Cable management



STANDARDS

Aginode specification

Functional characteristics	Fiber types	G.652.D or G.657.Ax (30 mm bending radius into cassettes)
	Admissible cables number and diameter	Feeder cables : 3 inputs for cables up to Ø14mm Drop cables : 16 outputs for cables Ø4-6mm The bottom plate managing cables inputs and outputs has been designed to be customized on demand for managing most of the cable sizes
	Splicing capacity	Up to 8 splice cassettes for a total of 96 splices
	Splitting capacity	Up to 6 splitters 1:8 or lower, Preterminated or not
	Patching capacity	Up to 48 OF patching, using 24 SC duplex adapters. LC adapters customized on demand

Cabinet overview










##image:113951:center##

- 1. Clamping kit
- 2. Coiling ring
- 3. Splitters holders
- 4. Patch panel
- 5. Coiling ring
- 6. Lock lever
- 7. Parking area
- 8. Organiser 8 cassettes (delivered as standard)
- 9. Seals
- 10. Network cable entry
- 11. Box

##image:114664:center##

##image:113952:center##

Provided Kits and combs

			Qté / Qty
Kit de fixation murale : – Supports de fixation – Vis hexagonale – Vis standard – Écrous		Wall mounting kit: – Mounting brackets – Hexagonal screws – Standard screws – Nuts	 4 8 4 4
Kit de fixation sur poteau : – Équerres de fixation – Rails en C – Cerclage métallique – Vis hexagonale – Écrous		Pole mounting kit: – Mounting brackets – C rails – Metallic strapping – Hexagonal screws – Nuts	 4 2 2 8 4
Kit de guidage des câbles : – Anneaux de lochage		Cables routing kit: – Coiling rings	 15
Kit d'arrimage : – Colliers plastique – Vis		Clamping kit: – Plastic ties – Screws	 12 6
Kit d'entrée et de sortie de câble : – Passe câbles à étages – Passe câble 4 trous – Rivets plastique – Vis en inox – Plaque métallique		Input and output cable kit: – Plugs – 4 holes grommet – Plastic rivets – Inox screws – Metallic plates	 3 4 2 4 2
Kit coupleur : – Support coupleurs – Plaque métallique – Élastique – Rivets plastique		Splitter kit: – Splitters holder – Metallic plate – Elastic – Plastic rivets	 1 1 1 2
Numéro du peigne Comb number		Ø des tubes ou pigtails Ø of tubes or pigtails	Qté / Qty
Peigne plastique Plastic comb		Ø 900µm	16
Peigne plastique #1 #2 #3 Plastic comb #1 #2 #3		Ø 1.6mm Ø 2.4mm Ø 2.8mm	3 3 3
Peigne plastique #5 Plastic comb #5		Ø 5mm	8

Metallic riser (optional)

In order to fix the PRE 24/48 on a concrete base, as and stand alone cabinet, a metallic riser can be supplied in option.

Aginode Reference : 10279503

##image:113953:left##

Pole mounting kit (optional)

As an option, the PRE 24/48 can be delivered with a pole mounting kit.

Aginode Reference: 10279749

##image:113975:center##

PRE 48 OF

Characteristics

Construction characteristics

Colour	Light grey RAL 7035
Material	Polyester loaded with glass fibre

Dimensional characteristics

Depth	200 mm
Height	400 mm
Length	300 mm
Cable Diameter, range	... mm
Max. number of cassettes	8
Splice number	96
Approximate net weight	6.3 kg
Maximum number of adaptators	48
Diameter main cable	3...14 mm

Mechanical characteristics

IK Rating	10
-----------	----

Usage characteristics

Operating temperature, range	-25...70 °C
U.V resistance	Yes
Installation type	Indoor/Outdoor
Watertightness	IP 55

ドキュメンテーション

PRE 48 installation pdf — 7.68 MB [ダウンロード ↓](#)

販売および配送情報

Delivery in unit package. Metallic riser for stand alone installation sold and delivered separately.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.