

Duct - Microbundle cables

MICROBUNDLE RSM CABLE 3X12SM SP1868


This ruggedized cable is used for Access, Distribution, City Network and FTTx applications. It is designed to be quickly installed by pulling, blowing and on aerial

Characteristics & Applications

- Ruggedized cable design
- Easy installation with mid span access possibility
- Easy micro bundle stripability
- Glass yarns and radial strength members reinforcement
- All dielectric design
- Waterproof structure

Construction

- Jelly filled microbundles containing coloured fibres
- Radial FRP strength members
- Glass yarns reinforcement
- Water swellable tape
- HDPE outer sheath



STANDARDS

EN 187000
IEC 60794

Microbundle RSM cable 3x12SM SP1868

Characteristics

Construction characteristics

Fiber optic type	SM
Armour type	Glass yarns
Outer sheath	HDPE
Sheath colour	Black - UV
Metal free	Yes
Strength member	Embedded FRP
Construction type	Multibundle

Dimensional characteristics

Number of tubes	3
Approximate weight	60 kg/km
Number of optical fibres	36
Nominal outer diameter (mm)	8.6 mm

Mechanical characteristics

Maximum admissible traction load (Tm)	188 daN
Crush resistance (IEC 60794-1-E3)	250 N/cm

Usage characteristics

Operating temperature, range	-30...70 °C
Storage temperature, range	-40...70 °C
Ambient installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.