

# LANmark-OF Pigtailed Tight Buffer Set of 12 Colours

LANMARK-OF PIGTAIL LC/UPC SINGLEMODE TIGHT BUFFER LSZH 9/125 2M 12 COLOURS

**Aginode Ref:** N121.4TLS2


- Factory terminated fibre assembly
- Tight Buffer pigtail: 1-2cm stripping in one action
- Set of 12 pigtailed with different jacket colours
- Insertion loss per connection without splice: typical 0,1 dB; 0.25 dB maximum
- 100 % factory tested
- Compatible with LANmark-OF splice cassette with heat shrink protectors.

## Pigtail set characteristics

- Fibre assembly to terminate cable with fusion splicing
- Suitable for use in patch panels using splice cassettes
- The pigtailed can be stripped in one action over a distance of 1-2cm
- Jacket colours match fibre colours according to TIA/EIA-598-B
- Jacket colours: Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Turquoise
- 12 pigtailed on a cardboard and wrapped in a bubblefoam

## Fibre type

- The LANmark-OF OM3 pigtailed have LANmark-OF OM3 **GIGALite FLEX** fibre inside. This bend insensitive multimode fibre has a small bend radius of 7,5 mm and is compliant to IEC 60793-2-10, fibre model A1a.2b.
- The LANmark-OF OM4 pigtailed have LANmark-OF OM4 **GIGALite FLEX** fibre inside. This bend insensitive multimode fibre has a small bend radius of 7,5 mm and is compliant to IEC 60793-2-10, fibre model A1a.3b.
- The LANmark-OF SM pigtailed have LANmark-OF SM **GIGALite FLEX** fibre inside. These fibres are bend insensitive and compliant to ITU-T G.657.A1 and to IEC 60793-2-50, fibre model B6.a1.



## STANDARDS

ISO/IEC 11801

## Compatibility and installation practices

- Tight buffer pigtails are compatible with heat shrink splice cassettes (N890.090 and N890.095) with heat shrink protections (N890.021).
- Tight buffer pigtails are recommended to be used with tight buffer cables, i.e. with 900 um fibres. When using loose tube cables (250 um fibres) additional stress on the loose tube fibres should be limited as much as possible
- Around the splice area the pigtail needs to be stripped till the cladding before insertion in the splice tool.
- For proper alignment in the fusion splice tool the pigtail is fixed on the 900 um outer sheath. There is no need to strip the outer sheath of the pigtail on the place for fixation for getting a proper fixation.

## Guarantees

Aginode LANmark-OF pigtails are covered by Aginode warranty as described in the General Terms and Conditions.

# LANmark-OF Pigtail LC/UPC Singlemode Tight Buffer LSZH 9/125 2m 12 Colours

## Characteristics

### Construction characteristics

Fiber optic type	SM (G657.A1)
Connector type	LC

### Transmission characteristics

Insertion Loss, maximum, dB	0.25 dB
Return Loss, Minimum, dB	50 dB

## ドキュメンテーション

SM G657 A1 bis\_2.xls xls — 21.5 KB [ダウンロード ↓](#)