

# Essential-6 Cable

## ESSENTIAL-6 U/UTP CAT 6 LSZH 23AWG 305M REEL IN BOX

**Aginode Ref:** N100.170

- Unshielded construction
- Complies to latest Category 6 standards
- Central cross maintains geometry and performance
- Supports Class E applications up to 250 MHz.

## Application

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

## Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

## Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

**Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel. (Values specified at 20°C)**



## STANDARDS

ANSI/TIA-568-C.2  
EN 50288  
IEC 61156-5  
ISO/IEC 11801-1

# Essential-6 U/UTP Cat 6 LSZH 23AWG 305m reel in box

## Characteristics

### Construction characteristics

Outer sheath	LSZH
Type of cable	U/UTP
Colour	Orange

### Dimensional characteristics

Conductor cross-section (AWG/KCMIL)	23
Nominal outer diameter (mm)	6.1 mm
Diameter over insulation	1.0 mm

### Electrical characteristics

Max. DC resistance of the conductor at 20°C (Ohm/km)	93.8
Mutual capacitance	56 nF/km
Characteristic impedance	100 Ohm

### Mechanical characteristics

Maximum operating pulling force	100 N
---------------------------------	-------

### Transmission characteristics

Propagation delay, max. 100 MHz	536 ns/100m
Skew	45 ns/100m

### Usage characteristics

Packaging	Reel in a box
Field of application	Indoor
Operating temperature, range	-20...60 °C
Minimum Bend Radius - During Installation (under Tension)	49 mm
Minimum Bend Radius - Installed	25 mm
Smoke density	IEC 61034
Ambient installation temperature, range	-10...60 °C
Category	Cat. 6
Range	essential-6
Length	305 m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Flame retardant

IEC 60332-1

## ドキュメンテーション

Freetable Ess6 channel.xls xls — 14 KB [ダウンロード ↓](#)