
# LANmark-OF UC 屋外用 PE 2～24コア APAC地域

**LANMARK-OF UC PE 12コア OM4 ブラック APAC地域**




**Aginode Ref:** N177.185

ダクト内や地中直埋設に適しています

- 波形鋼帯アーマー
- ゲル充填チューブ
- マルチモードおよびシングルモードファイバーに対応
- 齧歯類からの保護機能を備えています
- 外被材はHDPE

## 概要と用途

Aginode LANmark-OF
UC光ファイバーケーブルは、屋外用途向けに設計されています。その構造は、屋外での直埋設に適しています。本製品は、波形鋼帯アーマーで保護されたユニケーブルの外被にはHDPEが使用されています。

## 構造

断面図の凡例：

1. 光ファイバー（250 µm）
2. 防水ゲル充填
3. ルーズチューブ
4. ガラスヤーン
5. 波形鋼帯アーマー
6. 耐紫外線添加剤を配合したHDPE外被

## 特徴

- スプライシングによる終端処理を想定して設計
- 中央ルーズチューブ構造
- 波形鋼製保護層
- 防水構造かつ耐紫外線性あり
- マルチモードおよびシングルモードファイバーに対応
- 2～24ファイバーのラインナップ

## STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF UC PE 12コア OM4 ブラック APAC地域

## Characteristics

| | |
|---|---|
| **Construction characteristics** | |
| Outer sheath | HDPE |
| Sheath colour | Black |
| Armour type | Galvanized steel tapes |
| **Mechanical characteristics** | |
| Mechanical resistance to impacts (IEC 60794-1-E4) | 100 impacts of 1 N.m |
| Maximum pulling force (IEC 60794-1-2-E1) | 1300 N |
| Crush resistance (IEC 60794-1-E3) | 300 N/cm |
| **Usage characteristics** | |
| Storage temperature, range | -30...60 °C |
| Operating temperature, range | -20...60 °C |
| Minimum dynamic operating bending radius | 164.0 mm |
| Minimum static operating bending radius | 82 mm |
| Ambient installation temperature, range | 0...40 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*