LANmark-OF MPO-MPO プレターム OFNP 方式 C APAC

LANMARK-OF メソッド C MPO/M-MPO/M プレターム SM OS2 G.657.A1 96C OFNP XXXM 片側イエロー引き目



Aginode Ref: N144.CU96SAxxx-PY

- 工場出荷時に接続済みのMPO-MPOファイバーアセンブリ
- パッチパネルへの設置を容易にする柔軟なファンアウト構造
- ケーブル径が小さいため、データセンターに必要なスペースを削減
- 方式Cの極性、事前終端済み
- デュプレックス伝送に必要なパッチコードとカセットは、それぞれ1種類のみ
- ファイバー本数：96F
- ファイバータイプ：シングルモード OS2 G.657.A1

??????????????????????????????????????
??
????
??
MPO-MPO ????????
MPO-MPO ??? Plug&Play
????????????????????????????????
N ????xxx??
??
???????????MPO??450N??
????????????????????? N890.100HP ????????????
MPO????????????????????????????????????
MPO-MPO????????LANmark-OF Plug&Play?????????????????PG-13?????????????????
????????
???????? MPO-MPO ??? ???? ?????0.5 dB ????????? 0.75 dB ???MPO-MPO ?????????IEC61300-3-45 ?????????????
???????MPO???????????IEC 61300-3-6???????????45 dB???
????C??TIA-568.3-D-2016?????C?????????

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF メソッド C MPO/M-MPO/M プレターム SM OS2 G.657.A1 96c OFNP xxxM 片側イエロー引き目

Characteristics

Construction characteristics	
Fiber optic type	SM (G657.A1)
Dimensional characteristics	
Number of optical fibres	96
Nominal outer diameter (mm)	10.0 mm
Mechanical characteristics	
Maximum installation tension	1000 N
Mechanical resistance to impacts	10 impacts of 3 N.m
Crush resistance (IEC 60794-1-E3)	100 N/cm
Transmission characteristics	
Insertion Loss, maximum, dB	0.75 dB
Return Loss, Minimum, dB	45 dB
Usage characteristics	
Operating temperature, range	-20...60 °C
Minimum dynamic operating bending radius	20 (xD)
Minimum bending radius, static (XD)	10

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.