
LANmark-OF TB OFNP 2-48C - アジア太平洋地域

LANMARK-OF タイトバッファ 屋内用 12芯 マルチモード 50/125 BI OM4 プレナム、OFNP



Aginode Ref: N177.025NP

- タイトバッファ型屋内用光ファイバーケーブル 屋内用ケーブル
- 施工性を高めるアラミド糸
- 直接終端およびスプライシングに対応した設計
- 12ファイバー
- OM4ケーブル用曲げ耐性ファイバー

用途

LANmark-OF Tight buffer Indoorは、900
umのバッファ層を備えたファイバーを採用しています。この2層目の
900 µmまでのこの2層目の被覆は、ファイバーをさらに保護するとともに、
パッチパネルでのファイバー終端処理時の取り扱いを容易にします。剥離が容易なタイトバッファ
設計により、1回の動作で10
cm以上のファイバーをストリッピングできます。
LANmark-OF タイトバッファ・インドアは、
。また、タイトバッファ光ファイバは、
ピグテールのスプライシングによる終端処理も可能です。
LANmark-OF
タイトバッファ・インドアは、そのドライ構造により、垂直および
水平設置の両方が可能です。屋内用光ファイバーの要件に準拠しています。このケーブルは
は、引き込み方式によりダクト内にも敷設可能です。

構造

断面図の凡例：

1. 光ファイバー（900 um）
2. アラミド繊維
3. PVC OFNP素材の外被

STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF タイトバッファ 屋内用 12芯 マルチモード 50/125 BI OM4 プレナム、OFNP

Characteristics

Construction characteristics	
Fiber optic type	OM4 50/125
Colour	Aqua
Dimensional characteristics	
Number of optical fibres	12
Outer Diameter	6 mm
Weight	34 g
Mechanical characteristics	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	460 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Usage characteristics	
Installation temperature, range	0...40 °C
Storage temperature, range	-30...70 °C
Operating temperature, range	-20...60 °C
Minimum dynamic operating bending radius	120.0 mm
Minimum static operating bending radius	60 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.