LANmark-OF MPO-MPO パッチコード

LANMARK-OF MPO-MPO パッチコード、OM3、ストレート、MPOメス-MPOメス、12芯、LSZH、アクア、低損失、2M



Aginode Ref: N125.5SLA2

- AginodeのMPOパッチコードは、外径3mmのスリムなケーブル設計を採用しており、これによりデータセンターのユーザーは、パネル前面
- AginodeのMPOコネクタの光性能は業界水準を上回っており、国際規格に準拠しています
- 曲げに強靭なOM3に対応しています
- TIA 568.C.3に準拠したストレート極性（タイプB）
- 両端にメス型MPOコネクタを採用しています。

用途

AginodeのMPOパッチコードは、40G、100G、200G、400Gなどのデータセンター向け高速ネットワーク用途に対応するように設計されて
このMPOケーブルは外径（OD）が最適化されており、優れた引張強度と耐圧性能を維持しています。各MPOトランクには、性能を保証す

- MPOコネクタは、IEC 61754-7-1およびGR-1435-CORE規格に準拠しています。
- マルチモード用MPOコネクタはPCタイプです。
- OFケーブルはIEC 60794規格に準拠しています。ケーブルはLSZH素材であり、IEC 60332-1、IEC 60332-3-24、IEC 61034-2、およびIEC 60754-1・2に準拠しています。
- ファイバーはIEC 60793-2-10（A1a.2b OM3）に準拠しています

STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO パッチコード、OM3、ストレート、MPOメス-MPOメス、12芯、LSZH、アクア、低損失、2m

Characteristics

Construction characteristics	
Fiber optic type	OM3 50/125
Transmission characteristics	
Insertion Loss, maximum, dB	0.35 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.