LANmark-OF ボウファイバーケーブル 1-2C

FTTH ボウ型ドロップケーブル 2F LSZH、ブラック

Aginode Ref: N174CH.002

- 床の配線に最適
- 曲げ半径の小さいファイバー
- ノッチ構造によりコアが取り出しやすい
- 難燃性（IEC 60332-1 および IEC 60332-3C 準拠）



特徴

特殊な低曲げ感度ファイバーにより、広い帯域幅と優れた通信伝送特性を提供します。

シングルモード G657A2 の性能：IEC60793-2-10、サブタイプ
B6a.2 に準拠

斬新なフルート設計により、被覆の剥ぎ取りや接続が容易で、設置やメンテナンスが簡素化されます。

構造

断面図の凡例：

1. 光ファイバー
2. FRP
3. LSZH素材の外被

STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FTTH ボウ型ドロップケーブル 2F LSZH、ブラック

Characteristics

Construction characteristics	
Fiber optic type	SM (G657.A2)
Colour	Black
Dimensional characteristics	
Number of optical fibres	2
Width	3 mm
Weight	8 g
Height	2 mm
Mechanical characteristics	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	80 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Transmission characteristics	
Attenuation, max. 1310 nm (cabled)	0.5 dB/1000m
Attenuation, max. 1550 nm (cabled)	0.4 dB/1000m
Usage characteristics	
Storage temperature, range	-20...60 °C
Operating temperature, range	-20...60 °C
Minimum static operating bending radius	15 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.