LANmark-OF アグリゲーション・アセンブリ MPO-4DLC

LANMARK-OF MPO-4DLC ファンアウト・パッチコード、OM3、LSZH、アクア、低損失、2M

Aginode Ref: N127.5BLAA2



- AginodeのMPOパッチコードは、外径3mmのスリムなケーブル設計を採用しており、これにより、データセンターのユーザーは、Aginode
- Aginode MPOコネクタの光性能は業界水準を上回り、国際規格に準拠しています。
- 曲げに強靭なOM3に対応
- 片側がメス型MPOコネクタ、もう片側がデュプレックス・ユニブートLCコネクタとなっています。

用途

AginodeのMPO-
4DLCファンアウトパッチコードは、40G、100Gといった集約アプリケーションや、400Gなどの将来のアプリケーションに対応するように設計されています。Ag
このMPOケーブルは外径（OD）が最適化されており、優れた引張強度と耐圧性能を維持しています。

- MPOコネクタは、IEC 61754-7-1およびGR-1435-
  CORE規格に準拠しています。
- マルチモード用MPOコネクタはPCタイプです。
- OFケーブルはIEC 60794規格に準拠しています
- LC コネクタは、より優れたファンアウト管理を実現するために Uniboot
  設計を採用しています。
- ケーブルは LSZH 素材で、IEC 60332-1、IEC 60332-3-24、IEC61034-
  2、および IEC 60754-1 および 2に準拠しています。
- ?????? IEC 60793-2-10 (A1a.2b OM3) ????????
- MPO ?????OM3 ?????? 0.35dB??? 0.25dB
- DLC ?????OM3 ?????? 0.25dB??? 0.15dB

STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-4DLC
ファンアウト・パッチコード、OM3、LSZH、アクア、低損失、2m

Characteristics

Construction characteristics	
Fiber optic type	OM3 50/125
Dimensional characteristics	
Outer Diameter	3 mm
Mechanical characteristics	
Maximum tensile load	100 N
Usage characteristics	
Storage temperature, range	-40...70 °C
Operating temperature, range	-10...60 °C
Flame retardant	IEC 60332-1; IEC 60332-3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.