

# B-LITE LT - マイクロルース・チューブ・ケーブル

MICROCABLE 12X12SM 200MM SP2007

**Aginode Ref:** Microcable 12x12SM 200µm SP2007 BLite LT


This compact cable is used for Access, Distribution, City Network and FTTx applications. It is designed to be quickly installed by blowing in micro-ducts.

## Characteristics & Applications

- High blowing distance due to the excellent friction properties of the outer sheath
- Right balance between flexibility and rigidity
- Easy installation with mid span access possibility
- Central strength member reinforcement
- All dielectric design
- Waterproof structure

## Construction

- Jelly filled microloose tubes containing coloured fibres
- Central FRP strength member
- Very Low friction outer sheath



## STANDARDS

EN 187000  
IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# Microcable 12x12SM 200µm SP2007

## Characteristics

### Construction characteristics

Fiber optic type	G657A1 - 200 µm
Outer sheath	PA
Metal free	Yes
Strength member	FRP
Construction type	Multitube

### Dimensional characteristics

Number of tubes	12
Approximate weight	39 kg/km
Number of optical fibres	144
Nominal outer diameter (mm)	6.6 mm

### Mechanical characteristics

Maximum tensile load during service (Tl)	20.0 daN
Maximum admissible traction load (Tm)	100 daN
Crush resistance (IEC 60794-1-E3)	100 N/cm

### Usage characteristics

Operating temperature, range	-30...60 °C
Storage temperature, range	-40...70 °C
Installation type	Outdoor - Microduct blowable
Ambient installation temperature, range	0...40 °C
Bending factor when laying	20 (xD)

## ドキュメンテーション

White Paper Microblown Cable pdf — 1.94 MB [ダウンロード ↓](#)

## 販売および配送情報

## Standard Marking

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode - FIBRE OPTIC CABLE - SPxxxx - XX\*YY - FB - TN - metric

XX = Fibre Count

YY = Fibre Type

FB = Produced in Frameries, Belgium

TN = Traceability Number

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*