LANmark-OF MPO Base8 事前組立品

LANMARK-OF MPO BASE8 プレターミネーションアセンブリ 方式B OM3 48F 低損失 LSZH アクア シングルエンド 牽引ハンドル XXXM

Aginode Ref: N145Q.BL48LAxxx-LA



- 工場で終端処理済みのBase8 MPOファイバーアセンブリ
- パッチパネルへの設置を容易にする柔軟なファンアウト構造
- ケーブル径が小さいため、データセンターに必要なスペースを削減
- データセンターの基準を満たす難燃性LSZHケーブル
- MPOケーブルの規格はMETHOD Bですが、METHOD A、METHOD B、METHOD Cなど、他の極性規格も選択可能です。
- 40G/100G/200G 並列伝送に最適化
- 8/16/24/48/72/96 コアから選択可能
- オプションで、曲げに強いうるつら多モードBI OM3/OM4/OM5ファイバーおよびG.657.A1準拠のOS2ファイバーが利用可能で、G.652.Dファイバーと完全な互換性があります

STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

Micro-Bundle Universal ??????????????????????????????
??
????
???????IEC 60332-3c?????????????????????????LSZH???????????
MPO-MPO Pre-Term???
??????????????
???????????MPO?????????????????????????Plug&Play MPO-LC?????????????????????????????????
??1m???????????N????xxx??
Pre-Term???MPO??450N???
MPO????????LANmark-OF Plug&Play?????????????????????PG-13???????????????????
??????
??????MPO???????????0.2 dB?????????????????0.35 dB???MPO??????????IEC 61300-3-45?????????????
??????MPO???????????IEC 61300-3-6???????????20 dB???
????B??TIA-568.3-D-2016?????B?????????

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO Base8 プレターミネーションアセンブリ 方式B OM3 48F 低損失 LSZH アクア シングルエンド 牽引ハンドル xxxm

Characteristics

Construction characteristics	
Fiber optic type	OM3 50/125
Dimensional characteristics	
Number of optical fibres	48
Transmission characteristics	
Insertion Loss, maximum, dB	0.35 dB
Return Loss, Minimum, dB	20 dB
Usage characteristics	
Operating temperature, range	-20...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.