

# Railways - Multibundle K209 cables

MBC K209B LSZH 24X12SM G657A1 SP1921 BK

**Aginode Ref:** MBC K209B LSZH 18x12SM SM SP1921 BK

Multi Micro-bundles cable with corrugated steel armour - 288 fibres

This multi micro-bundles cable is designed for indoor/outdoor installation in railways infrastructure.

The corrugated steel armour provides a high rodent protection. This cable has an outstanding fire behaviour.

Access to  $\mu$ bundles is made easy with the internal ripcord.

This cable can be operated under a large temperature range.

## Design

The MBC LSZH SP1921 cable has a central strength member (FRP : Fibre Reinforced Plastic), with 24 bundles around integrating 12 fibres each. The design is reinforced by a first layer of watertight glass, a LSZH\* inner sheath, a second layer of watertight glass yarns, a corrugated steel armour and a LSZH\* outer sheath.

## Technical performances

The multibundle cable performances are specified in the following tables.

## Euroclass

B2<sup>ca</sup> S1a a1 d0

\* LSZH: Low Smoke Zero Halogen.



## STANDARDS

EN 50399 B2  
IEC 60331-2  
IEC 60332-1  
IEC 60332-3  
IEC 60754-1  
IEC 60794  
IEC 61034

# MBC K209B LSZH 24x12SM G657A1 SP1921 BK

## Characteristics

### Construction characteristics

Colour	Black
Fiber optic type	OS2
Armour type	Corrugated steel
Outer sheath	LSZH
Halogen free	IEC 60754-1
Material used for longitudinal water tightness	Swellable yarn
Metal free	No
Strength member	Central FRP
Construction type	Multibundle
Additional strength member	Glass yarn

### Dimensional characteristics

Number of tubes	18
Approximate weight	330 kg/km
Number of optical fibres	192
Nominal outer diameter (mm)	16.7 mm

### Mechanical characteristics

Mechanical resistance to impacts	3 impacts of 5 N.m
Maximum permanent tensile load	3.4 kN
Crush resistance (IEC 60794-1-E3)	200 N/cm
Maximum installation tension	5700 N

### Usage characteristics

Rodent protection	Corrugated steel tape
Operating temperature, range	-30...60 °C
Fire resistant	EN50200 PH120 or IEC60331-25**
Fire retardant	IEC 60332-3
Minimum static operating bending radius	330 mm
Flame retardant	IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

U.V resistance	Good
Storage temperature, range	-30...70 °C
Laying operation bending radius	420 mm
Installation type	Indoor/Outdoor
Installation temperature, range	-5...60 °C
Water proof	Longitudinal & radial

## パフォーマンス宣言

MBC K209B LSZH 24x12SM G657A1 SP1921 BK pdf — 119.68 KB [ダウンロード ↓](#)

## 販売および配送情報

## Standard Marking

Aginode - FIBRE OPTIC CABLE - MBC LSZH SPxxxx - XXxYY - FB - TN - metric

XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number