

# UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 72 LC (48MM + 24SM) / 50M

**Aginode Ref:** 13200649

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- High mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

## Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

## Installation

- Indoor and outdoor
- LSZH-FR

## Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# UPSKY™ preterminated cable 72 LC (48MM + 24SM) / 50m

## Characteristics

### Construction characteristics

Colour	Black
Outer sheath	LSZH-FR (Dca s2 do)
Construction type	Multitube à porteur central
Fibre optic type	SM G657 A2 or OM3
Additional strength member	Glass yarn

### Dimensional characteristics

Approximate weight	85 kg/km
Number of optical fibres	72
Cable Diameter	8.9 mm

### Mechanical characteristics

Mechanical resistance to impacts	5N.m
Crush resistance	100daN/cm kg/cm
Maximum Pulling Tension	200daN (80 daN) kN

### Usage characteristics

Storage temperature, range	-40...70 °C
Installation type	Indoor/Outdoor
Installation temperature, range	0...40 °C