

UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 24 LC (16MM + 8SM) / 100M

Aginode Ref: 13200650

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- High mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

Installation

- Indoor and outdoor
- LSZH-FR

Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UPSKY™ preterminated cable 24 LC (16MM + 8SM) / 100m

Characteristics

Construction characteristics

| | |
|----------------------------|--|
| Colour | Black |
| Outer sheath | LSZH-FR (Dca s2 do) |
| Construction type | Multitube with central strenght member |
| Fibre optic type | SM G657 A2 or OM3 |
| Additional strength member | Glass yarn |

Dimensional characteristics

| | |
|--------------------------|----------|
| Approximate weight | 85 kg/km |
| Number of optical fibres | 24 |
| Cable Diameter | 8.9 mm |

Mechanical characteristics

| | |
|----------------------------------|--------------------|
| Mechanical resistance to impacts | 5N.m |
| Crush resistance | 100daN/cm kg/cm |
| Maximum Pulling Tension | 200daN (80 daN) kN |

Usage characteristics

| | |
|---|----------------|
| Minimum static operating bending radius | 178 mm |
| Storage temperature, range | -40...70 °C |
| Installation type | Indoor/Outdoor |
| Installation temperature, range | 0...40 °C |
| Operating temperature flexing, range | 30...60 °C |