ウォールドロップ V2

WALLDROP ウィンドウ保護クリップ

Aginode Ref: 13200411 - 14500789

- Aginodeファサードソリューションの一部
- ファイバー切断点でケーブルを保護
- ファイバー取り出しプロセスでWALLDROPボックスに付随
- ファサードでの屋外使用向けに設計
- 再利用可能



窓保護クリップはAginodeファサードソリューションの一部です。WALLDROPファサードボックスの繊維取り出し工程をサポートします。

2つのプラスチック部品で構成されています：

-

ファサード配電ケーブルの後ろに配置され、シールとケーブルクランプ装置をサポートする部品（プラスチックタイUV保護付き）

-

もう1つは、4つのクリップで付属品を確実に閉じるための部品です。

窓保護クリップは、WALLDROPファサードボックスと同じシーリングシステムを採用しています。したがって、6〜12mmのファサードケ

ケーブル開口部100mmまでの防水性を保証します。

保護等級はファサードでの屋外使用が可能です（IP55 / IK07）。

このアクセサリーは、将来的なメンテナンスの際にも再挿入が可能です。



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

WALLDROP ウィンドウ保護クリップ

Characteristics

Construction characteristics	
Colour	Black
Material	Thermoplastic
Dimensional characteristics	
Diameter branch cable	3...7 mm
Diameter main cable	10...12 mm
Height	33 mm
Length	177 mm
Max. number of cables	1
Max. number of cassettes	1
Splice number	12
Width	28 mm
Mechanical characteristics	
IK Rating	7
Usage characteristics	
Installation type	Outdoor
Minimum static operating bending radius	15 mm
Operating temperature, range	-40...65 °C
Packaging	Box
RoHS compliant	Yes
U.V resistance	Yes
Watertightness	IP 55

ドキュメンテーション

Instruction manual pdf — 5.25 MB　ダウンロード

Leaflet Facade Solution EN pdf — 5.07 MB　ダウンロード

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.