ウォールドロップ V2

WALLDROP ポール取り付けブラケット

Aginode Ref: 13200235



ポール巻取り装置はWALLDROPボックスと組み合わせて使用します。この装置は、オーバーレングスを管理し、空中配電ケーブルを確実に

- 加入者接続用ポールアプリケーション（最大10件まで）
- マイクロモジュールケーブルに対応（48OF mod6まで）
- G657A2ファイバー対応
- 材質：塗装ステンレススチール（黒色）

WALLDROPボックスは、光ケーブルの配線を可能にするために設計されています。そのデザインにより見た目のインパクトが少なく、最大
標準仕様として12接続用のスプライスカセットを装備しており、接続を中断することなく現場で36接続まで拡張することができます（拡張
ドロップ・ケーブル・エントリーには、3〜7mm（3〜5mmと5〜7mmをシールする2タイプ）の開口部に対応するシーリング・プラグ付
オーガナイザートレイは、メインケーブルと加入者接続部から取り出されたファイバーまたはマイクロモジュールのための個別の巻取りソ
スプライスカセットには1x4ベアファイバースプリッター用のスロットがあります。
WALLDROPボックスは、設置場所に応じて水平にも垂直にも取り付けることができます。また、ケーブルに直接吊り下げて設置することも
製品には、設置に必要なすべての付属品（コーム、カセット、シール、プラスチックタイ、壁取り付けキット）が同梱されています。
ライトグレーとブラックの2色からお選びいただけます。



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

WALLDROP ポール取り付けブラケット

Characteristics

Construction characteristics	
Colour	Black
Material	Stainless Steel
Dimensional characteristics	
Height	43 mm
Width	295 mm
Length	200 mm
Max. number of cables	10
Max. number of cassettes	3
Splice number	12
Diameter main cable	6...12 mm
Diameter branch cable	3...7 mm
Mechanical characteristics	
IK Rating	8
Usage characteristics	
Operating temperature, range	-40...65 °C
Minimum static operating bending radius	7.5 mm
U.V resistance	Yes
Packaging	Box
Installation type	Outdoor
RoHS compliant	Yes
Watertightness	IP 55

ドキュメンテーション

Instruction manual pdf — 5.25 MB　ダウンロード

Leaflet Facade Solution EN pdf — 5.07 MB　ダウンロード

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.