

# Essential-6 Patch Panels

## ESSENTIAL-6 PCB PATCH PANEL UNSCREENED 24 RJ45 CAT 6 REAR CONNECT BLACK WITH CABLE SUPPORT BAR

**Aginode Ref:** N500.206CH

- Complies to the latest Category 6 standard
- 24 unshielded RJ45
- Punchdown termination from the rear
- Colour: Black
- UL listed
- Printed numbering for port labelling
- Labelling window
- Supplied with cable support bar, fixings, cable ties, cable stripping tool and IDC dust cover

## Application

The Aginode Essential-6 patch panels are based on 19" frame dimensions and have 24 Category 6 RJ45 ports on 1HU. They support Class E applications up to 250 MHz. When the panels are installed in conjunction with Essential-6 cable and outlets, a 25 year Class E Link Certificate can be obtained from the Aginode e-service site.

## Design

The Essential-6 patch panels are compatible with the complete Essential-6 range and can be used with all types of UTP Category 6 cable with solid wire from 22 to 24 AWG.

## Performance

The Essential-6 patch panels are compliant with the specifications of ISO/IEC 11801 and IEC 60603-7.

## Installation

- Fast and easy termination of IDC blocks by LSA+ punchdown tooling.
- Colour code T568A and T568B (Product dependent).
- Supplied with cable support bar, fixings, cable ties, cable stripping tool and IDC dust cover.



## STANDARDS

IEC 60603-7-4  
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Contact resistance:	max. 20 m Ohm
Input to output DC resistance:	max. 200 m Ohm
Insulation resistance:	min. 500 M Ohm
Voltage proof:	1000 V DC or AC peak, contact to contact
Mating cycles:	min. 750
Insertion cycles:	min. 20
Insertion and withdrawal force:	max. 20 N

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# Essential-6 PCB Patch Panel Unscreened 24 RJ45 Cat 6 Rear Connect Black with Cable Support Bar

## Characteristics

### Construction characteristics

Connector type RJ45 and 110/LSA+ IDC

### Dimensional characteristics

Depth 132 including the cable support bar mm

Height unit 1 U

### Usage characteristics

Category Cat. 6

Component function Patch panel

Number of ports 24

Range essential-6

## Documentation

[Freetable Cat6 UNSHIELDED connectors additional characteristics.xls xls](#) — 22 KB [ダウンロード ↓](#)

### Installation manual - N500.206CH

[N500.206CH Aginode installation guide.pdf pdf](#) — 3.02 MB [ダウンロード ↓](#)