

LANmark Power-OF Cable 1.5 mm²

LANMARK POWER-OF 2X1,5 WHITE

Aginode Ref: NFP1.A24A2A-WE

Hybrid cable with optical fibres and power conductors, designed for fixed installations requiring high fire performance.

- 2 x G.657.A2 fibres (Ø 0.9 mm)
- 2 x 1.5 mm² copper conductors
- White LSZH sheath – UV resistant
- Indoor cable

Hybrid cable integrating optical and power transmission in a single compact design. Each function is built as a separate sub-unit:

Fibre Unit

- 2 to 4 single-mode fibres (G.657.A2)
- Tight buffer Ø 0.9 mm
- Aramid yarns
- LSZH flame-retardant sheath Ø 2.0 mm

Power Unit

- 2 x 1.5 mm² stranded bare copper
- LSZH flame-retardant insulation Ø 2.9 mm
- Water-blocking tape
- LSZH sheath Ø 7.0 mm – UV resistant

General

- Outer sheath: white LSZH
- Standards: **RoHS 2011/65/EU, REACH EC 1907/2006**

Application:

- Indoor routing



STANDARDS

EN 50575
IEC 60228

LANmark Power-OF 2x1,5 White

Characteristics

Construction characteristics

| | |
|---------------------|--|
| Insulating material | EN 50290-2-26 (LSZH) |
| Colour | Data : blue and green - Power : black and blue |

Dimensional characteristics

| | |
|----------------|--------------|
| Nominal weight | 90 kg/km g/m |
|----------------|--------------|

Electrical characteristics

| | |
|---------------------------------|----------------------------------|
| Maximum rated voltage | 450/750 V (U _o /U) kV |
| Conductor electrical resistance | 13.3 Ω/km (@ 20°C) Ohm/km |
| Test voltage | no break down V |
| Insulation resistance | 0.01 MΩ/km (@70°C) GOhm.km |

Mechanical characteristics

| | |
|------------------------------|------------------------|
| Crush resistance | 300 N (Plate/plate) kN |
| Maximum installation tension | 150 N |

Transmission characteristics

| | |
|---------------------------|-----------------|
| Maximum/typical @ 1310 nm | 0.40/0.34 db/km |
| Maximum/typical @ 1550 nm | 0.25/0.20 db/km |
| Maximum/typical @ 1625 nm | 0.40/0.22 db/km |

Usage characteristics

| | |
|--|-------------|
| Installation temperature, range | -15...50 °C |
| Storage temperature, range | -40...70 °C |
| Minimum dynamic operating bending radius | 82 mm |
| Minimum bending radius, static (XD) | 42 |
| Maximum operating temperature | -30...70 °C |
| Fire resistant | . |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.