DCmark Rack Unit Solution Collocation DC

DCMARK RACK UNIT SOLUTION COLLOCATION DC 42U 3 COMPARTMENTS



Aginode Ref: NRL3.420808340-B

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

Rack are equipped with 3 compartments of 13U; each have a single front perforated door, lockable by key. Each key have a specific number for the confidentiality.

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

The Rack N.RCL3 is equipped with 3 compartments of 13U with a total loading capacity of 1500Kg. Each compartment have a single front perforated door and double rear perforated door.

To ensure a high confidentiality of the tenant, each compartment have is own key with a specific number printed on the barrel (Aginode is the only part knowing the correspondace between this code and the key number).

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

DCmark Rack Unit Solution Collocation DC 42U 3 compartments

Characteristics

Construction characteristics	
Cabinet format	19"
Compartment number	3 x 13U
Colour	Black
Cable entry	Entrée supérieure via passe-fil balai et chemin de câble fermé
Material	Steel
Rack version	Collocation
Type of front door	Simple porte AV perforée
Type of rear door	Double porte AR métal
Dimensional characteristics	
19'' mounting	Avant & Arrière
Compartment Height U	13U
Height	2017 mm
Width	800 m
Approximate net weight	150 kg
Depth	800 mm
Heightunit	42 U
Mechanical characteristics	
IK Rating	07
Usage characteristics	
Locking system	Clé individuelle par compartiment
IP Rating	IP20
Key type	Numéro spécifique & unique

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.