# LANmark-OF MPO Base8 事前組立品

**LANMARK-OF ENSPACE BASE8 プレターム シングルモード OS2 メソッドB MPO8 オス-MPO8 オス 8コア LSZH イエロー 低損失 プルアイなし XXXM**

**Aginode Ref:** N144.B8L08SPxxx-LY

- 工場で終端処理済みのBase8 MPOファイバーアセンブリ
- パッチパネルへの設置を容易にする柔軟なファンアウト構造
- ケーブル径が小さいため、データセンターに必要なスペースを削減
- データセンターの基準を満たす難燃性LSZHケーブル
- MPOケーブルの規格はMETHOD Bですが、METHOD A、METHOD B、METHOD Cなど、他の極性規格も選択可能です。
- 100G/400G 並列伝送に最適化
- 8/32/48 コアから選択可能
- オプションで、G.657.A1に準拠した曲げに強靭なマルチモードBI OM3/OM4/OM5ファイバーおよびOS2ファイバーを選択可能。G.652.Dファイバーと完全互換



## STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

**????????????????????????????????FO????**
????????????????????????????????????????????????
**????**
???????IEC 60332-3c????????????????????????LSZH???????????
**MPO-MPO Pre-Term???**
Pre-Term???????????????MPO????????????????????????MPO-LC????????????????????????????????
????????????????????????????????????1m???????????N????xxx????????????????????????????????????????????????????????????
Pre-Term????????????????????????????????????MPO????????????????????????????????????????????450N???
MPO????????LANmark-OF ENSPACE Base8????????????????????????Base8????????????????????
**??????**
??????MPO???????????0.5 dB???????????????????0.75 dB???MPO??????????IEC 61300-3-45?????????????
??????MPO???????????IEC 61300-3-6???????????45 dB???
????B????????????????????????????????????????ANSI/TIA-568.3-E?????B?????????

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF ENSPACE Base8 プレターム シングルモード OS2 メソッドB MPO8 オス-MPO8 オス 8コア LSZH イエロー 低損失 プルアイなし xxxm

## Characteristics

| | |
|---|---|
| **Construction characteristics** | |
| Fiber optic type | SM(G.657.A1) |
| **Dimensional characteristics** | |
| Number of optical fibres | 8 |
| **Transmission characteristics** | |
| Insertion Loss, maximum, dB | 0.75 dB |
| Return Loss, Minimum, dB | 45 dB |
| **Usage characteristics** | |
| Operating temperature, range | -20...60 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*