

# LANsense TGA Optical Fiber Patch Panels

## LANSENSE TGA OPTICAL FIBER PATCH PANEL 48 LC/LC MULTIMODE BLACK

**Aginode Ref:** NLS3.PLC48A

- TGA optical fiber patch panel 48 LC/LC black in color
- Pre-assembled patch panel, convenient for installation
- Multimode OM4 fiber type
- The top-to-down closing dust cover with detection function
- 48-core duplex LC optical fiber channel
- Specially optimized for the installation of pre-terminated fiber cables
- The label attached is convenient for port identification and patching
- Each port has LED lights to assist with the working operation

The new pre-assembled LC/LC patch panel is suitable for installation in buildings and data centers.

The patch panel is pre-installed with a LC adapter, providing 48 LC channels for front-end connection and supporting fusion splicing and cable fixation of optical fibers.

The multimode type of this patch panel is black in color.

The OM4 LC adapter is aqua green; the LED light on the port can assist in simple working operation, facilitating patching and patching tracing.

This optical fiber patch panel can monitor the insertion and removal of patch cables through the dust cover.

The dust cover also protects the LC adapter from dust ingress.

The RJ45 I/O ports at the rear-end of the optical fiber patch panel allow.



### STANDARDS

ISO/IEC 11801

# LANsense TGA optical fiber patch panel 48 LC/LC multimode black

## Characteristics

### Construction characteristics

Colour	Black
Connector type	LC
Fiber optic type	Multimode

### Dimensional characteristics

Depth	268.6 mm
Heightunit	1 U
Number of optical fibres	48

### Transmission characteristics

Insertion Loss, maximum, dB	0.25 dB
Return Loss, Minimum, dB	20 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.