
LANmark-OF DB 屋外用 LSZH 2〜144芯 APAC地域

LANMARK-OF 屋外用DB光ファイバーケーブル、シングルモード G.652.D 9/125 48F、LSZH、黒、APAC地域向け

Aginode Ref: N174.48DBLH

- ダクト内や地中埋設などの屋外用途に適しています
- 防水素材を採用した堅牢な構造
- OM3/OM4/OS2のファイバーに対応、最大144コア
- 二重金属テープアーマリングにより、げっ歯類からの完全な保護を実現
- ゲル充填ルーズチューブ



STANDARDS

ANSI/TIA-568.3-D
IEC 60794
ISO 11801 Ed.3

製品説明

DB屋外用ケーブルは、ダクト内や直埋設での屋外用途に適しています。本ケーブルは、ルースチューブ内のゲルおよびケーブル内部の防水
ケーブルの外被はLSZH素材で、IEC 60332-1、IEC 60332-3-
24、IEC 61034-2、IEC 60754-
1/2の規格に準拠しています。ファイバーの直径は250 umです。
ファイバーの終端処理は、ピグテールのスプライシングによって行うことができます。

構造

断面図の凡例：
1. 光ファイバー（250 µm）
2. チューブ充填材
3. ルースチューブ
4. アルミニウムテープ装甲
5. 防水材
6. LSZH外被
7. スチールテープ装甲
8. LSZH内被覆
9. 充填材
10. 中心補強材
11. 防水材

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF 屋外用DB光ファイバーケーブル、シングルモード G.652.D 9/125 48F、LSZH、黒、APAC地域向け

Characteristics

Construction characteristics	
Outer sheath	LSZH
Sheath colour	Black
Armour type	Double Metal Tape
Mechanical characteristics	
Mechanical resistance to impacts (IEC 60794-1-E4)	10 impacts of 10 N.m
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Crush resistance (IEC 60794-1-E3)	3000 N/100mm
Usage characteristics	
Storage temperature, range	-40...70 °C
Operating temperature, range	-40...70 °C
Minimum dynamic operating bending radius	166 mm
Minimum static operating bending radius	332 mm
Ambient installation temperature, range	0...40 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.