# Transition adapters

**FIBREROUTE 360MM(14.17 INCH)-240MM(9.45 INCH) REDUCER**

**Aginode Ref:** N350.360FT02A

Aginode Fiber Trunking System provides a dedicated pathway for fiber optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data center containment which is easy to install and reconfigure to meet future needs.



- Pathway system designed for accommodation of data center fiber cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Reducer allows the interconnection of 240mm(9.45 inch) and 360mm(14.17 inch) systems
- Tough, flame retardant ABS material

The Aginode Fiber Trunking System provides a dedicated pathway through data center spaces and IT facilities for routing fiber cables.
The rigid channel with matching cover protects fiber optic cables from damage.
All components of the system are made of tough, fire retardant materials.
The system components have a smooth inner surface to ensure a safe path for fiber optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.
All components of the system including the covers can be installed and uninstalled without special tools.

## STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# FIBREROUTE 360mm(14.17 inch)-240mm(9.45 inch) Reducer

## Characteristics

| | |
|---|---|
| **Construction characteristics** | |
| Material | PVC |
| Colour | Yellow |
| **Dimensional characteristics** | |
| Width | 396 mm |
| Depth | 118 mm |
| Length | 204.5 mm |
| **Usage characteristics** | |
| Storage temperature, range | -45...60 °C |
| Operating temperature, range | -25...60 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*