
LANmark-OF DB 屋外用 PE 2-144芯 APAC地域

LANMARK-OF 屋外用DB光ファイバーケーブル、マルチモード OM3 50/125 48F、PE、黒、APAC地域向け

Aginode Ref: N175.48DBPE

- ダクト内や直埋設など、屋外での使用に適しています
- 防水材を採用した堅牢な構造
- OM3/OM4/G.652.D/G.657.A1のファイバーに対応、最大144コア
- 二重金属テープ装甲により、げっ歯類からの完全な保護を実現
- ゲル充填ルーズチューブ



製品説明

DB屋外用ケーブルは、ダクト内や直埋設での屋外用途に適しています。本ケーブルは、ルースチューブ内のゲルおよびケーブル内部の防水ケーブルの外被はPE製で、耐紫外線性および耐候性に優れています。ファイバーの直径は250 umです。ファイバーの終端処理は、ピグテールのスプライシングによって行うことができます。

構造

断面図の凡例：

1. 光ファイバー（250µm）
2. チューブ充填材
3. ルースチューブ
4. アルミニウムテープ装甲
5. 防水ゲル
6. PE外被
7. スチールテープ装甲
8. PE製内ジャケット
9. 充填材
10. 中央補強部材
11. 防水ゲル

STANDARDS

ANSI/TIA-568.3-D
IEC 60794
ISO 11801 Ed.3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF 屋外用DB光ファイバーケーブル、マルチモード OM3 50/125 48F、PE、黒、APAC地域向け

Characteristics

Construction characteristics	
Armour type	Double Metal Tape
Outer sheath	PE
Sheath colour	Black
Mechanical characteristics	
Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Mechanical resistance to impacts (IEC 60794-1-E4)	10 impacts of 10 N.m
Usage characteristics	
Ambient installation temperature, range	0...40 °C
Minimum dynamic operating bending radius	332 mm
Minimum static operating bending radius	166 mm
Operating temperature, range	-40...70 °C
Storage temperature, range	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.