Floor Splicing: @XS-BOX M

- Indoor splicing box
- Version 1 OF/Sub. with tray 12/24OF
- Version 2-4 OF/Sub. with 1 à 4 trays 2-4OF
- Output for drops up and down
- Installation vertically or horizontally
- Aesthetic and ergonomic



STANDARDS

IEC 61753-1

The @XS-BOX M line is designed to manage the building distribution of a riser cable to subscribers as part of FTTH deployments.

Main functions :

- Clamping of riser cable Ømax 14mm to right or left* with open cable protection and on-demand fiber extraction management
- Clamping of up to 24 drop cables Ømax 5mm, 12 at the top and 12 at the bottom*
- Management and protection of fibers and splices in 2 architectures 1OF/Sub. or 2-41OF/Sub.
- Horizontal or vertical wall mounting by screws (provided) inside or outside the housing

* Stowage by plastic collars (provided) with possibility to fix carriers and / or aramids of the cable

Composition :

The @XS-BOX M is built around a base and a cover, to which are added the cassettes answering to the selected wiring architecture.
Optionally, it can incorporate 2 ¼ turn screws to secure the closure.

Cabling :

The @XS-BOX M is optimized for extraction installation, but it is also compatible with termination and midspan configurations.
In the body, various zones of coiling make it possible to

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

manage bundles and 900µm fibers connected or waiting to avoid any incident when connecting a new subscriber.
The 2 configurations proposed allow a connection of the Subscribers on demand in a common tray of capacity 12/24 splices compatible fibers G652D / G657A or in 1 to 4 double-sided trays of capacity 4 splices by face (1 Subscriber by face therefore max 8 Subscribers) compatible G657A only.

@XS-BOX M 12-24 with 1OF/Sub.



@XS-BOX M with double-side trays 2-4OF/Sub.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



Accessory - Cover extension kit

##image:110716##

These covers are used to fix the @XS-BOX M along a PVC cable way to have a perfect finish by hiding drop and riser cables.

The kit is composed with 2 covers for up and down.

Aginode reference : **10192633**

Accessory - Sealing kit

##image:110717##

These sealing is used to have a better protection regarding dust and water, it gives to the @XS-BOX M an IP level at IP42.

The kit is composed with 4 sealing, 2 small for riser and 2 wider for drops to protect up and down.

Aginode reference : **10179110**

Accessory - Wall spacer

##image:110718##

These sealing is used to have a better protection regarding dust and water, it gives to the @XS-BOX M an IP level at IP42.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

The kit is composed with 4 sealing, 2 small for riser and 2 wider for drops to protect up and down.

Aginode reference : **10179110**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Floor Splicing: @XS-BOX M

CHARACTERISTICS

구조적 특성	
Fiber optic type	SM (G.652D)
치수	
Depth	42 mm
Height	180 mm
Width	125 mm
기계적 특성	
IK Rating	8
사용 특성	
操作温度范围	-10...60 °C
Fire resistant	UL 94 V0
Watertightness	IP 42

Resources

문서

@XS-BOX M double side trays instruction manual pdf — 2.63 MB 다운로드

판매 및 배송 정보

Unit packaging in plastic bag

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	이름
	10284661	-	@XS-BOX M 2.0 12-24 splices
	10284776	-	@XS-BOX M 2.0 12-24 splices with 1/4 turns secured cover
	10283788	-	@XS-BOX M 2.0 equiped with 1 double side cassette for 12 OF
	10283912	-	@XS-BOX M 2.0 equiped with 2 double side cassettes for 24 OF
	10284044	-	@XS-BOX M 2.0 equiped with 3 double side cassettes for 36 OF
	10283789	-	@XS-BOX M 2.0 equiped with 4 double side cassettes for 48 OF

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.