

Voice Cables APAC

- 25pr, 50pr, or 100pr
- Suitable for voice and low grade data
- Category 3 and Category 5 compliant

Voice grade cables are used to integrate telephony applications in the backbone of a LAN infrastructure. They are multipair twisted pair cables and exist in Category 3, Category 5 and Category 5e performance levels.



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Voice Cables APAC

CHARACTERISTICS

구조적 특성

피복 저연 할로겐 프리

Type of cable U/UTP

치수

Number of pairs 25

사용 특성

Category Cat. 3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	이름	피복	Type of cable	Number of pairs	Category
☎ N100.817N-3	-	Voice U/UTP 25 pair AWG24 Cat 3 LSZH-FRT Orange reel	저연 할로겐 프리	U/UTP	25	Cat. 3
☎ N100.819N-3	-	Voice U/UTP 100 pair AWG24 Cat 3 LSZH-FRT Orange reel	저연 할로겐 프리	U/UTP	100	Cat. 3
🏠 N100.818N	-	Voice U/UTP 50 pair AWG24 Cat 3 LSZH Orange reel	저연 할로겐 프리	U/UTP	50	Cat. 3
🏠 N100.819N	-	Voice U/UTP 100 pair 24 AWG Cat 3 LSZH Orange Reel	저연 할로겐 프리	U/UTP	100	Cat. 3
☎ N100.M22	-	Voice U/UTP 25 pair AWG24 Cat 5e LSZH Orange 1000m reel	저연 할로겐 프리	U/UTP	25	Cat. 5e
🏠 N100.817N	-	Voice U/UTP 25 pair AWG24 Cat 3 LSZH Orange reel	저연 할로겐 프리	U/UTP	25	Cat. 3
☎ N100.837N	-	Voice U/UTP 25 pair AWG24 Cat 3 PE 1000m reel	폴리에틸렌	U/UTP	25	Cat. 3
🏠 N100.838N	-	Voice U/UTP 50 pair AWG24 Cat 3 PE 1000m reel	폴리에틸렌	U/UTP	50	Cat. 3
☎ N100.818N-3	-	Voice U/UTP 50 pair AWG24 Cat 3 LSZH-FRT Orange reel	저연 할로겐 프리	U/UTP	50	Cat. 3

☎ = Make to order, 🏠 = In Stock