
# LANmark-OF UGUN (Unitube - Universal) Dca

- Unitube indoor/outdoor cable
- Good fire performance
- Reaction to fire: Dca-s1,d2,a1 according to EN50575:2014+A1:2016
- Large operation temperature range






## STANDARDS

ISO/IEC 11801

### Description and Application

The cable is designed for indoor and outdoor installation. The design is made of a central loose tube surrounded by reinforcing yarns and a LSZH jacket incorporating 2 lateral strength members.

The cable is watertight due to the gel in the loose tube and the watertight swellable yarns.

The UGUN contains up to 24 fibres (Diameter 250µm). Termination of these fibres is done with splicing of pigtails.

### Construction

Legend accompanying the cross section drawing:

- 1.Central loose tube with 250 µm fibres
- 2. Gel
- 3. Reinforcing yarns
- 4. Lateral strengths members
- 5. LSZH Outer sheath

### Features

- Indoor / Outdoor cable
- Designed for termination by splicing
- Unitube design with Lateral Strength Elements
- Full dielectric design
- Waterproof structure
- UV Resistant
- Wide temperature range

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF UGUN (Unitube - Universal) Dca

## CHARACTERISTICS

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*