# PRE: 24/48 Distribution Cabinet

Indoor / Outdoor Distribution Cabinet:

- versions for 24 or 48 subscribers
- installation on wall, pole or stand alone with a metallic riser (optional)
- Built-in wall box for discrete installation
- 1 cassette dedicated to splitters (patched or spliced)
- from 2 to 8 cassettes for subscriber management
- suitable for PON as P2P network architectures
- robustness and sobriety



## STANDARDS

Aginode specification

The PRE 24/48 is a distribution cabinet designed to adapt to as much ground configuration as possible. Its use makes it possible to reduce the complexity of the deployments by proposing a unique reference which can be fixed on a wall, a pole or a riser as an autonomous cabinet.

The PRE 24/48 can be used indoors as well as outdoors (IP55).

Capacity

2 standard configurations are available: 24 or 48 OF. The number of cassettes, each accommodating up to 12 splices, is adapted to your needs and the network architecture used (PON or P2P).

Patching and splicing

3 separate zones make it possible to manage the body of the splitters (SOD), the conectors of the subscriber cables, and the coiling or splicing of the main and secondary cables (or pigtails). Depending on your needs, the PRE 24/48 can be configured in both patching and splicing versions.

Quality materials

While the body of the PRE 24/48 is made of polyester reinforced with fiberglass ensuring a lightness, waterproofness (IP55) and shock abatement (IK10), the moving parts are metallic to guarantee an optimal lifetime of the assembly when intensive uses.

## Cable management

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| Functional characteristics | | |
|---|---|---|
| | **Fiber types** | G.652.D or G.657.Ax (30 mm bending radius into cassettes) |
| | **Admissible cables number and diameter** | Feeder cables : 3 inputs for cables up to Ø14mm<br>Drop cables : 16 outputs for cables Ø4-6mm<br>*The bottom plate managing cables inputs and outputs has been designed to be customized on demand for managing most of the cable sizes* |
| | **Splicing capacity** | Up to 8 splice casettes for a total of 96 splices |
| | **Splitting capacity** | Up to 6 splitters 1:8 or lower. Preterminated or not |
| | **Patching capacity** | Up to 48 OF patching, using 24 SC duplex adapters. LC adapters customized on demand |

## Cabinet overview

##image:113951:center##

- 1. Clamping kit
- 2. Coiling ring
- 3. Splitters holders
- 4. Patch panel
- 5. Coiling ring
- 6. Lock lever
- 7. Parking area
- 8. Organiser 8 cassettes (delivered as standard)
- 9. Seals
- 10. Network cable entry
- 11. Box

##image:114664:center##

##image:113952:center##

## Provided Kits and combs

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| | | Qté / Qty |
|---|---|---|
| Kit de fixation murale : | *Wall mounting kit:* | |
| – Supports de fixation | – *Mounting brackets* | **4** |
| – Vis hexagonale | – *Hexagonal screws* | **8** |
| – Vis standard | – *Standard screws* | **4** |
| – Écrous | – *Nuts* | **4** |
| Kit de fixation sur poteau : | *Pole mounting kit:* | |
| – Équerres de fixation | – *Mounting brackets* | **4** |
| – Rails en C | – *C rails* | **2** |
| – Cerclage metallique | – *Metallic strapping* | **2** |
| – Vis hexagonale | – *Hexagonal screws* | **8** |
| – Écrous | – *Nuts* | **4** |
| Kit de guidage des câbles : | *Cables routing kit:* | |
| – Anneaux de lovage | – *Coiling rings* | **15** |
| Kit d'arrimage : | *Clamping kit:* | |
| – Colliers plastique | – *Plastic ties* | **12** |
| – Vis | – *Screws* | **6** |
| Kit d'entrée et de sortie de câble : | *Input and output cable kit:* | |
| – Passe câbles à étages | – *Plugs* | **3** |
| – Passe câble 4 trous | – *4 holes grommet* | **4** |
| – Rivets plastique | – *Plastic rivets* | **2** |
| – Vis en inox | – *Inox screws* | **4** |
| – Plaque metallique | – *Metallic plates* | **2** |
| Kit coupleur : | *Splitter kit:* | |
| – Support coupleurs | – *Splitters holder* | **1** |
| – Plaque métallique | – *Metallic plate* | **1** |
| – Élastique | – *Elastic* | **1** |
| – Rivets plastique | – *Plastic rivets* | **2** |

| **Numéro du peigne** *Comb number* | | **Ø des tubes ou pigtails** *Ø of tubes or pigtails* | Qté / Qty |
|---|---|---|---|
| Peigne plastique *Plastic comb* | Outil *Tool* | Ø 900µm | **16** |
| Peigne plastique #1 #2 #3 *Plastic comb #1 #2 #3* | | Ø 1.6mm<br>Ø 2.4mm<br>Ø 2.8mm | **3**<br>**3**<br>**3** |
| Peigne plastique #5 *Plastic comb #5* | | Ø 5mm | **8** |

## Metallic riser (optional)

In order to fixe the PRE 24/48 on a concrete base, as and stand alone cabinet, a metallic riser can be supplied in option.

**Aginode Reference : 10279503**

##image:113953:left##

## Pole mounting kit (optional)

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

As an option, the PRE 24/48 can be delivered with a pole mounting kit.

**Aginode Reference: 10279749**

##image:113975:center##

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# PRE: 24/48 Distribution Cabinet

## CHARACTERISTICS

| | |
|---|---|
| **구조적 특성** | |
| 색상 | 담회색 RAL 7035 |
| Material | 폴리에스터 유리 섬유 |
| **치수** | |
| Depth | 200 mm |
| Height | 400 mm |
| Length | 300 mm |
| Cable Diameter, range | ... mm |
| Max. number of cassettes | 8 |
| Splice number | 96 |
| Approximate net weight | 6.3 kg |
| Maximum number of adaptators | 48 |
| **기계적 특성** | |
| IK Rating | 10 |
| **사용 특성** | |
| 操作温度范围 | -25...70 °C |
| U.V resistance | Yes |
| Installation type | Indoor/Outdoor |
| Watertightness | IP 55 |

## Resources

### 문서

INSTRUCTIONS 24/48 DISTRIBUTION CABINET pdf — 3.37 MB 다운로드

INSTRUCTIONS METALLIC RISER pdf — 401.8 KB 다운로드

### 판매 및 배송 정보

Delivery in unit package. Metallic riser for stand alone installation sold and delivered separtely.

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

## Product list

| | Aginode ref. | Country ref. | 이름 | U.V resistance |
|---|---|---|---|---|
| | 10279411 | - | PRE 48 OF | Yes |
| | | - | PRE 24 OF | Yes |

= Make to order, = In Stock

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*