DCmark Slimflex 푸시-풀 LC-LC 광 패치 코드

- 광섬유 패치 코드
- 푸시풀 탭 또는 푸시풀 부트 설계
- 극성 전환 가능 커넥터
- 원형 케이블 설계
- GIGAliteFLEX 굴곡에 강한 광섬유 OM3/OM4/OM5/OS2 성능
- 캐비닛 및 작업장에서 사용



LANmark™

DCmark

STANDARDS

ISO/IEC 11801

용도

Aginode LANmark-OF SlimFlex PushPull 광 패치 코드는 고속 프로토콜을 지원하는 실내 용도로 설계되었습니다.
PushPull 탭 또는 PushPull 부트 디자인을 적용한 이 새로운 패치 코드는 별도의 도구 없이도 밀집된 패널에서 커넥터를 쉽게 삽입 및 분리할 수 있게 해줍니다. 또한 이 새로운 디자인은 현장 설치 요구 사항에 맞춰 극성을 신속하게 변경할 수 있습니다.
이 패치 코드는 굽힘에 강한 광섬유를 사용하여 10mm라는 매우 작은 굽힘 반경을 갖습니다. 패치 코드의 작은 굽힘 반경은 굽힘이 빈번한 고밀도 패칭 구역에서 유용합니다.
패치 코드의 원형 케이블 설계는 어떤 방향에서도 작은 굽힘 반경을 제공하며, 얇은 직경 덕분에 패치 코드에 필요한 공간을 40% 절감하여 공간 효율을 높이고, 냉각을 위한 기류 방해를 줄이며, 고밀도 환경에서 패치 코드 관리를 용이하게 합니다.

특성

- 패치 코드 케이블은 IEC 60794-2-50 규격을 준수합니다.
- IEC 61300-3-4에 따른 최대 삽입 손실: 0.25 dB
- 일반적인 삽입 손실: 0.15 dB
- IEC 61300-3-6에 따른 최소 반사 손실: 멀티모드의 경우 35 dB, 싱글모드의 경우 50 dB.
- 재킷 색상: OM5의 경우 라임 그린, OM3/OM4의 경우 아쿠아, OS2의 경우 노란색
- 이 광섬유는 굽힘에 민감하지 않은 유형이며, 굽힘 반경이 작습니다.

설계

Aginode LANmark-OF 패치 코드는 현장 설치 편의성을 높이기 위해 " 크로스오버" 배선 원리에 따라 설계되었습니다(A1-B2, B1-A2). 이는 IEC 11801 및 EN 50174-1:2009의 요구 사항을 준수합니다. 부트를 빼내고 2 개의 LC 커넥터 위치를 바꾸면 패치 코드의 극성을 변경할 수 있습니다.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

DCmark Slimflex 푸시-풀 LC-LC 광 패치 코드

CHARACTERISTICS

구조적 특성	
Fiber optic type	SM (G657.A1)
피복	저연 할로겐 프리
기계적 특성	
Maximum pushing force	200 N
Crush resistance (IEC 60794-1-E3)	100 N/cm
Transmission characteristics	
Insertion Loss, maximum, dB	0.25 dB
Return Loss, Minimum, dB	50 dB
사용 특성	
操作温度范围	-10...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	이름
	N122.4LCWYx	-	DCmark SlimFlex PushPull DLC 패치 코드, 극성 변경 가능, OS2 LSZH, xm, 노란색
	N122.7LCWVx	-	DCmark SlimFlex PushPull DLC 패치 코드, 극성 변경 가능, OM4 LSZH, xm, 바이올렛
	N122.5LCWAx	-	DCmark SlimFlex PushPull DLC 패치 코드, 극성 변경 가능, OM3 LSZH xm 아쿠아
	N128D.4LLBYxxx	-	DCmark Slimflex 부트 푸시-풀 듀플렉스 패치 코드 LC-LC OS2 LSZH 노란색 xx.xm
	N128D.7LLBVxxx	-	DCmark Slimflex 부트 푸시-풀 듀플렉스 패치 코드 LC-LC OM4 LSZH 보라색 xx.xm
	N128D.5LLBAxxx	-	DCmark Slimflex 부트 푸시-풀 듀플렉스 패치 코드 LC-LC OM3 LSZH 아쿠아 xx.xm
	N122.7LCWAx	-	DCmark SlimFlex PushPull DLC 패치 코드, 극성 전환 가능, OM4 LSZH xm 아쿠아

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.