

# LANmark-6 Cable

- Comply with all Category 6 cable standards
- Support Class E applications
- Central cross member maintains geometry and performance
- Tested up to 350MHz

## Application

Aginode LANmark-6 cables are the ideal solution for most of today's network requirements in normal office environments. They are manufactured and tested to the latest Category 6 specifications defined in the International and American cable standards and are designed to meet the quality and performance criteria needed to support all applications up to 250 MHz.

- 10baseT Ethernet
- 100baseTX Fast Ethernet
- 1000baseTX Gigabit Ethernet
- 155 MBit ATM
- 622 MBit ATM
- 1.2 Gbit ATM
- Future class E applications

## Design

The LANmark-6 cables have a central PE cross which helps maintaining the stability of the cable geometry and reduces the risk of a reduction in performance when bending the cable. The cables are available with a Dark Grey PVC or an Orange LSZH sheath. A various cables are available with different fire performance level.

## Performance

Tested to 350 MHz and with guaranteed performance to 250 MHz, Aginode LANmark-6 cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.



## STANDARDS

ANSI/TIA-568-C.2  
EN 50288  
IEC 61156-5  
ISO/IEC 11801-1

## Guarantees

The LANmark-6 cable performance is guaranteed to meet or exceed the requirements of the above mentioned standards.

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6 cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

## Electrical Performance LANmark-6 Cable

Freq. in MHz	IL in Db/100m		NEXT in dB		PSNEXT in dB		ACR-F in dB		PS ACR-F in dB		RL in dB	
	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
1	2,0	2,0	74,3	80,3	72,3	78,3	67,8	72,8	64,8	69,8	20,0	22,0
4	3,8	3,8	65,3	71,3	63,3	69,3	55,8	60,8	52,8	57,8	23,0	25,0
10	6,0	6,0	59,3	65,3	57,3	63,3	47,8	52,8	44,8	49,8	25,0	27,0
16	7,6	7,6	56,2	62,2	54,2	60,2	43,7	48,7	40,7	45,7	25,0	27,0
20	8,5	8,5	54,8	60,8	52,8	58,8	41,8	46,8	38,8	43,8	25,0	27,0
31,25	10,7	10,7	51,9	57,9	49,9	55,9	37,9	42,9	34,9	39,9	23,6	25,6
62,5	15,4	15,4	47,4	53,4	45,4	51,4	31,9	36,9	28,9	33,9	21,5	23,5
100	19,8	19,8	44,3	50,3	42,3	48,3	27,8	32,8	24,8	29,8	20,1	22,1
155	25,2	25,2	41,4	47,4	39,4	45,4	24,0	29,0	21,0	26,0	18,8	20,8
200	29,0	29,0	39,8	45,8	37,8	43,8	21,8	26,8	18,8	23,8	18,0	20,0
250	32,8	32,8	38,3	44,3	36,3	42,3	19,8	24,8	16,8	21,8	17,3	19,3
300	-	36,4	-	43,1	-	41,1	-	23,3	-	20,3	-	18,8
350	-	39,8	-	42,1	-	40,1	-	21,9	-	18,9	-	18,3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# LANmark-6 Cable

## CHARACTERISTICS

### 구조적 특성

피복	PVC - CM
Type of cable	U/UTP

### 치수

Conductor cross-section (AWG/KCMIL)	23
Nominal outer diameter (mm)	6.2 mm

### Transmission characteristics

Skew	45 ns/100m
Attenuation Crosstalk Ratio, 250MHz	5.5 dB/100m
Nominal Velocity of Propagation (NVP)	69 %
Propagation delay, max. 100 MHz	536 ns/100m

### 사용 특성

Range	LANmark-6
操作温度范围	-20...60 °C
Category	Cat. 6
난연	UL 1581 SEC. 1160 AND CSA FT4
Packaging	Reel in a box
Ambient installation temperature, range	-10...60 °C
최소 굽힘 반지름 - 설치시 (장력작용)	50 mm
최소 굽힘 반지름 - 설치 후	25 mm

## Resources

### 문서

Freetable LM6 cables\_Family\_2.xls xls — 23 KB [다운로드](#) ↓

## Product list

	Aginode ref.	Country ref.	이름	피복	Type of cable
☎	N100.614-D9	-	LANmark-6 U/UTP PVC CM 305m reel in box	PVC - CM	U/UTP
☎	N100.604-O6	-	LANmark-6 U/UTP LSZH IEC 60332-3-22 305m reel	저연 할로겐 프리 난연	U/UTP
🏠	N100.604	-	LANmark-6 U/UTP LSZH 305m reel in box	저연 할로겐 프리	U/UTP
🏠	N100.614	-	LANmark-6 U/UTP PVC 305m reel in box	폴리염화비닐	U/UTP
🏠	N100.672	-	LANmark-6 F/UTP LSZH 500m reel	저연 할로겐 프리	F/UTP
🏠	N100.661	-	LANmark-6 F2/UTP PVC 500m reel	폴리염화비닐	F <sup>2</sup> TP
☎	N100.662	-	LANmark-6 F2/UTP LSZH 500m reel	저연 할로겐 프리	F <sup>2</sup> TP
🏠	N100.617	-	LANmark-6 U/UTP PVC 305m Box	폴리염화비닐	U/UTP
🏠	N100.607	-	LANmark-6 U/UTP LSZH 305m Reelex Box	저연 할로겐 프리	U/UTP
☎	N100.604FR	-	LANmark-6 U/UTP LSZH IEC 60332-3-24 305m reel	저연 할로겐 프리 난연	U/UTP

☎ = Make to order, 🏠 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.