

WLB-Max : Indoor Wall Box

The WLB box range is designed to manage the infrastructure of passive solutions, ensuring efficient management of fibers and connections in network environments. It provides optimized cable organization, ensuring reliable and secure deployment.

Description

The WLB-Max is a compact and efficient fiber management solution designed for passive infrastructure cabling and other indoor fiber networks. It ensures secure connectivity, high-density fiber management, and easy maintenance.

Key Features

- **Modular Design:** Designed for easy integration in LAN environments.
- **High-Capacity Termination:** Supports up to up to 26 SC adapters.
- **Secure Access:** 8 mm triangular key locking system.
- **Quick Installation & Maintenance:** Tool-free door dismantling and front-access patching.
- **Robust Build:** Designed for reliable long-term indoor operation.

Applications

- Passive fiber optic infrastructure networks(GPON & P2P, FTTO...cet)
- Wall-mounted **fiber distribution point** for structured cabling

Disponible Version

- **Standard :** Comes with SC/APC adapters, ready for custom configurations.



STANDARDS

Aginode specification

WLB-Max : Indoor Wall Box

CHARACTERISTICS

구조적 특성

Cable entry	왼쪽부터
색상	담회색 RAL 7035
Material	플리카보네이트

치수

Depth	150 mm
Height	100 mm
Number of connectors	26
Width	450 mm

사용 특성

Adaptor	SC/APC
Locking system	Triangle
Minimum static operating bending radius	15 mm
操作温度范围	-25...70 °C
Packaging	Box

Product list

Aginode ref.	Country ref.	이름	Material	Number of connectors
NWLB.X026DU.W	-	WLB-Max - Standard	폴리카보네이트	26

☎ = Make to order, 📦 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.