

LANmark Power-OF Cable 1.5 mm²

Combining optical and electrical transmission in a single cable:

- **2 single-mode optical fibres** for high-speed data transmission
- **2 insulated copper conductors:**
 - Cross-sections: **1.5 mm²**
 - Designed for power supply
- **Available in two versions:**
 - **Indoor**
- **Fire-retardant sheath and insulation** ensuring safety in critical environments
- **UV-resistant outer jacket**

Fibre Optic Sub-Units

Designed for data transmission with enhanced mechanical protection:

- **Single-mode optical fibres**, compliant with ITU-T G.657.A2 standard
- **Tight-buffer coating** with **0.9 mm diameter**
- **Aramid yarns** for tensile strength and fibre protection
- **Halogen-free, flame-retardant PE sheath.**

Power Sub-Units

Engineered for low-voltage power delivery and robustness:

- **Stranded bare copper conductors**, **1.5 mm²** cross-section
- **Halogen-free, flame-retardant PE insulation,**
- **Water-blocking tape** for added protection against moisture ingress
- **Halogen-free, flame-retardant PE outer sheath,**
- **UV-resistant sheath** for outdoor durability



STANDARDS

EN 50575
IEC 60228

LANmark Power-OF Cable 1.5 mm²

CHARACTERISTICS

구조적 특성

Insulating material EN 50290-2-26 (LSZH)

색상 Data : blue and green - Power : black and blue

치수

Nominal weight 90 kg/km g/m

전기적 특성

Test voltage no break down V

Insulation resistance 0.01 MΩ/km (@70°C) GOhm.km

기계적 특성

Crush resistance 300 N (Plate/plate) kN

Product list

Aginode ref.	Country ref.	이름
NFP1.A24A2A-WB	-	LANmark Power-OF 2x1,5 B2ca White
NFP1.A24A2A-WC	-	LANmark Power-OF 2x1,5 Cca White
NFP1.A24A2A-WE	-	LANmark Power-OF 2x1,5 White

☎ = Make to order, 🏠 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.