LANmark WDZ-RYYP3 CU/LSZH/OS(AL)/LSZH Shielded Flame Retardant Flexible Cable

The LANmark Series of low-voltage cables are specialized cables designed for communication, signal transmission and low-voltage power supply of security equipment.
They are widely deployed in public security, monitoring projects, commercial buildings, residential buildings, smart homes and intelligent building systems.



Characteristic

- Copper Class 5
- Insulation of polyolefin, colored
- LSZH jacket
- Foil screen
- Nominal Voltage: U0/U=300/300V
- Temperature range: operation: -20°C ~ 70°C
  installation: 0°C ~ 50°C

Insulation color

Cores No.	color
2	Blue, Red
3	Blue, Red, Yellow/Green or Blue, Red, Green
4	Blue, Red, Green, Yellow/Green or Blue, Red, Green,Yellow
5	Blue, Red, Green,Yellow, Yellow/Green or Blue, Red, Green,Yellow, Black
6	Blue, Red, Green,Yellow, Black, Yellow/Green or Blue, Red, Green,Yellow, Black, Brown
7	Yellow jacket with number except Yellow/Green core.

Note: When there is a yellow/green ground wire in the core combination, The N-cord needs to add the suffix "G". The cross section will be using "G" to replace "x".

STANDARDS

IEC 60228
IEC 60754
IEC 61034
IEC 60332-1

TECHNICAL DATA

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

N – Code	Type	Cross section (mm²)	Insulation (mm)	Sheath (mm)	General OD. max	General OD. mix	Conductor Resistance 20°C / Ω/km	Insulation Resistance 70°C / MΩ.km
N10R13YW3205	WDZ-RYYP3	2x0.5	0.5	0.6	4.9	5.9	39.0	0.013
N10R13YW3305	WDZ-RYYP3	3x0.5	0.5	0.6	5.3	6.3	39.0	0.013
N10R13YW3405	WDZ-RYYP3	4x0.5	0.5	0.6	6.2	7.2	39.0	0.013
N10R13YW3505	WDZ-RYYP3	5x0.5	0.5	0.6	6.7	7.7	39.0	0.013
N10R13YW3605	WDZ-RYYP3	6x0.5	0.5	0.8	7.3	8.3	39.0	0.013
N10R13YW3207	WDZ-RYYP3	2x0.75	0.5	0.6	5.4	6.4	26.0	0.011
N10R13YW3307	WDZ-RYYP3	3x0.75	0.5	0.6	5.7	6.7	26.0	0.011
N10R13YW3307G	WDZ-RYYP3	3G0.75	0.5	0.6	5.7	6.7	26.0	0.011
N10R13YW3407	WDZ-RYYP3	4x0.75	0.5	0.8	6.7	7.7	26.0	0.011
N10R13YW3507	WDZ-RYYP3	5x0.75	0.5	0.8	7.3	8.3	26.0	0.011
N10R13YW3607	WDZ-RYYP3	6x0.75	0.5	0.8	7.9	8.9	26.0	0.011
N10R13YW3707	WDZ-RYYP3	7x0.75	0.5	0.8	7.9	8.9	26.0	0.011
N10R13YW3807	WDZ-RYYP3	8x0.75	0.5	0.8	8.6	9.6	26.0	0.011
N10R13YW3210	WDZ-RYYP3	2x1.0	0.6	0.6	6.1	7.1	19.5	0.010
N10R13YW3310	WDZ-RYYP3	3x1.0	0.6	0.8	6.9	7.9	19.5	0.010
N10R13YW3410	WDZ-RYYP3	4x1.0	0.6	0.9	7.8	8.8	19.5	0.010
N10R13YW3510	WDZ-RYYP3	5x1.0	0.6	0.9	8.5	9.5	19.5	0.010
N10R13YW3610	WDZ-RYYP3	6x1.0	0.6	1.0	9.5	10.5	19.5	0.010
N10R13YW3710	WDZ-RYYP3	7x1.0	0.6	1.0	9.5	10.5	19.5	0.010
N10R13YW3810	WDZ-RYYP3	8x1.0	0.6	1.0	10.2	11.2	19.5	0.010
N10R13YW3215	WDZ-RYYP3	2x1.5	0.6	0.8	7.1	8.1	13.3	0.010
N10R13YW3315	WDZ-RYYP3	3x1.5	0.6	0.8	7.5	8.5	13.3	0.010
N10R13YW3415	WDZ-RYYP3	4x1.5	0.6	0.9	8.4	9.4	13.3	0.010
N10R13YW3515	WDZ-RYYP3	5x1.5	0.6	1.0	9.4	10.4	13.3	0.010
N10R13YW3615	WDZ-RYYP3	6x1.5	0.6	1.0	10.3	11.3	13.3	0.010
N10R13YW3225	WDZ-RYYP3	2x2.5	0.7	1.0	8.7	9.7	7.98	0.009
N10R13YW3325	WDZ-RYYP3	3x2.5	0.7	1.0	9.3	10.3	7.98	0.009
N10R13YW3425	WDZ-RYYP3	4x2.5	0.7	1.0	10.2	11.2	7.98	0.009
N10R13YW3525	WDZ-RYYP3	5x2.5	0.7	1.1	11.4	12.4	7.98	0.009
N10R13YW3625	WDZ-RYYP3	6x2.5	0.7	1.1	12.4	13.4	7.98	0.009

Note: When there is a yellow/green ground wire in the core combination, The N-cord needs to add the suffix "G". The cross section will be using "G" to replace "x".

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.